



## **MATERIAL SAFETY DATA SHEET**



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 0456					
PRODUCT NAME: MACHINE DISH LIQUID L6					
USE: Machine Warewashing Detergent					
SUPPLIER: JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada		EMERGENCY PHONE: 1-800-668-7171			
WHMIS CLASSIFICATION:       D2B       E         CHEMICAL FAMILY:       caustic alkali		TRADE NAME / SYNONYMS:       not applicable         CHEMICAL NAME:       not applicable			
II - HAZARDOUS INGREDIENTS					
HAZARDOUS INGREDIENT	% w/w		CAS #	LD50 / LC50	Route / Species
Sodium hydroxide Sodium nitrilotriacetate	7-13 10-30		001310-73-2 005064-31-3	LDLo 500 mg/kg LD50 1100 mg/kg	oral/rab oral/rat
III - HANDLING AND DISPOSAL PROCEDURES					
Gloves:       Natural rubber, Neoprene or Nitrile       Eye:       s         Respiratory:       If mists are generated, use NIOSH approved mask         SPECIAL HANDLING PROCEDURES AND EQUIPMENT:         VENTILATION REQUIREMENTS:       General ventilation         INCOMPATIBILITY (Material to Avoid):       Acids, aluminum a         SPILL PROCEDURES:       Contain the spill. Do not allow the subscription with large volumes         WASTE DISPOSAL:       Dispose according to municipal, province         STORAGE / SHIPPING REQUIREMENT:       Store in a cool dry	Avoid eye a nd soft meta spilled produ of water. tial, and fede	rubbei Ind skin als. Ict to go Ict regul	to drain. Mop up or so ations.		ay for disposal.
IV - PHYSICAL PROPERTIES APPEARANCE / ODOUR: Clear red liquid					
S.G. / BULK DENSITY(g/cc): 1.27			<b>pH:</b> (1% solution): 12.2		
VAPOUR PRESSURE (mmHg): not available			VAPOUR DENSITY (air=1): not available		
ODOUR THRESHOLD: not applicable		BOILING POINT: approx. 100°C			
FREEZING POINT: approx10°C		PERCENT VOLATILE: 68%			
SOLUBILITY IN WATER: soluble			EVAPORATION RATE (water=1): 1		
V - TOXIC	COLOGIC	AL PR	OPERTIES		
EFFECTS OF ACUTE EXPOSURE TO MATERIAL:         EYES:       Corrosive. May cause severe irritation. May cause         SKIN:       Corrosive. May cause severe irritation. May cause         INGESTION:       Corrosive. May cause severe irritation of the dig	use tempora gestive tract.	ry or per May ca	manent damage if not use permanent damag	treated promptly.	
INHALATION: Corrosive. Inhalation of spray or mist may cause severe res			LC50 (calculated): not applicable		
LD50 (calculated): LD50 2588 mg/kg			LUDU (calculated): not applicable		

OTHER TOXIC EFFECTS: TLV-CL (Sodium hydroxide): 2 mg/m3						
<b>EFFECTS OF CHRONIC</b> <b>EXPOSURE TO MATERIAL:</b> This product contains NTA. In laboratory tests, rats and mice continuously fed highly exaggerated doses of NTA showed evidence of urinary tract (bladder and kidney) toxicity, including cancer; lower doses showed none of these toxic effects. By ACGIH guidelines, NTA would not be considered an occupational (human) carcinogen of any practical significance.						
VI - FIRST AID MEASURES						
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.						
<b>SKIN:</b> Flush affected area thoroughly with water. If irritation develops, contact a physician.						
<b>INGESTION:</b> Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.						
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.						
VII - FIRE AND EXPLOSION DATA						
FLAMMABLE: No						
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE,°C: N/Ap					
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []						
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.						
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, nitrogen	٦.					
EXPLOSIVE SENSITIVITY TO: not applicable						
VIII - REACTIVITY DATA						
STABILITY: Stable [x] Unstable [ ]						
CONDITIONS TO AVOID: not applicable						
INCOMPATIBILITY (Material to Avoid) : Acids, aluminum and soft metals.						
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with acids. Contact with aluminum or zinc generates hydrogen gas. Nitrogen oxides, carbon monoxide.						
REACTIVITY: not dangerously reactive						
IX - MSDS PREPARATION						
SOURCES USED: RTECS, ChemInfo	PREPARED BY: JohnsonDiversev Canada. Inc. Regulatory Department					
PREPARATION DATE: April 15, 2003	Institutional Division Phone (905) 829-1200					
Information on this form is furnished in compliance with the Regulations re not to be used for any other purpose, nor is it to be reproduced or published person or property resulting from any use of the material if reasonable safe assumes no responsibility for injury to any person or property resulting from procedures are followed. Each user assumes the risk in his use of the material context of the intended use.	d. JohnsonDiversey Canada assumes no responsibility for injury to any ty procedures are not adhered to. In addition, JohnsonDiversey Canada n any abnormal use or theft of the material, even if reasonable safety					