



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 0458

PRODUCT NAME: ALUMINUM SAFE DISH LIQUID L7**USE:** Machine Warewashing Detergent**SUPPLIER:**JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada**EMERGENCY PHONE:****1-800-668-7171****WHMIS CLASSIFICATION:** D2B E**CHEMICAL FAMILY:** Chlorinated Alkali**TRADE NAME / SYNONYMS:** not applicable**CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Potassium hydroxide	10-30	001310-58-3	LD50 273 mg/kg	oral/rat
Sodium hypochlorite (10.5%-solution)	10-30	007681-52-9	LD50 4445 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Natural rubber, Neoprene or Nitrile **Eye:** safety goggles **Footwear:** not required

Respiratory: If mists are generated, use NIOSH approved mask **Other:** not required

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact.**VENTILATION REQUIREMENTS:** General ventilation.**INCOMPATIBILITY (Material to Avoid):** Acids, ammonia, urea, amines.**SPILL PROCEDURES:** Wear protective clothing. Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.**WASTE DISPOSAL:** Dispose according to municipal, provincial, and federal regulations.**STORAGE / SHIPPING REQUIREMENT:** Store in a cool dry area in a closed container. UN3266

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear pale yellow liquid - chlorine odour**S.G. / BULK DENSITY(g/cc):** 1.30**pH:** 13.5 ± 0.5**VAPOUR PRESSURE (mmHg):** not available**VAPOUR DENSITY (air=1):** not available**ODOUR THRESHOLD:** 0.2-0.4 ppm chlorine**BOILING POINT:** approx. 100°C**FREEZING POINT:** approx. -10°C**PERCENT VOLATILE:** approx. 69%**SOLUBILITY IN WATER:** soluble**EVAPORATION RATE (water=1):** 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**EYES:** Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.**SKIN:** Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.**INGESTION:** Corrosive. May cause severe irritation of the digestive tract. May cause permanent damage if not treated promptly.**INHALATION:** Corrosive. Inhalation of spray or mist may cause severe respiratory irritation.**LD50 (calculated):** LD50 2235 mg/kg**LC50 (calculated):** not applicable

OTHER TOXIC EFFECTS: TLV - CL (Potassium hydroxide): 2 mg/m3; TLV (Chlorine) - TWA: 0.5 ppm; STEL: 1 ppm	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.
INHALATION:	Remove patient to fresh air. Get medical attention for any breathing difficulty.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: No	
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.	
HAZARDOUS COMBUSTION PRODUCTS: Chlorine gas and oxygen released when heated.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [] Unstable [x]	
CONDITIONS TO AVOID: Chlorine loss accelerated at high temperature and when exposed to light.	
INCOMPATIBILITY (Material to Avoid) : Acids, ammonia, urea, amines.	
HAZARDOUS DECOMPOSITION PRODUCTS: Contact with acid generates heat and chlorine gas. Contact with ammonia, urea and amines produces nitrogen gas and chloramines.	
REACTIVITY: not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: RTECS, ChemInfo	PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	