
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

VAH 204

MSDS ID: 04608

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Product Descriptor:

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
-----	-----	-----	-----	-----
VAH 204		>30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: MAY IRRITATE EYES. PROLONGED CONTACT MAY IRRITATE SKIN.

CHRONIC: SAME AS ACUTE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Sensitive skin

IV. FIRST AID MEASURES

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): >200

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, WATER FOG

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

SOAK UP SMALL SPILLS WITH ABSORBENT. COLLECT AND RETURN LARGE AMOUNTS TO CONTAINER. AREA MAY BE SLIPPERY; TAKE PRECAUTIONS TO PREVENT FALLS. KEEP SPILL OUT OF SEWERS AND OPEN BODIES OF WATER.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: KEEP CONTAINER CLOSED. DO NOT STORE ABOVE 140F. KEEP OUT OF REACH OF CHILDREN.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

VAH 204

MSDS ID: 04608

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: IMPERVIOUS
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: NORMAL AIR DILUTION
LOCAL VENTILATION: YES

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

BOILING POINT (DEG F): 212	FREEZING POINT: Not determined
SPECIFIC GRAVITY/BULK DENSITY:	
pH:	pH 1% SOLUTION: Not Determined
VOLATILE BY VOLUME: 42	
VAPOR PRESSURE(mmHg): N/A at 20 C	VAPOR DENSITY: <1

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: OXIDES OF CARBON AND TOXIC MONOMER FUMES.
HAZARDOUS DECOMPOSITION PRODUCTS: None known.
HAZARDOUS POLYMERIZATION: NONE KNOWN

XI. TOXICOLOGICAL INFORMATION

No data available.
TOXICITY TEST DATA:
No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA: No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

VAH 204**MSDS ID: 04608**

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: Lb/Gal VOC:

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: A

NFPA RATING: HEALTH: FIRE: REACTIVITY: SPECIAL:

STATE RIGHT-TO-KNOW INFORMATION:

*ACRYLIC COPOLYMER (UNASSIGNED)

WATER - CAS #7732-18-5

MINERAL OIL - CAS #8042-47-5

SILICA - CAS #763-18-69

PROPYLENE GLYCOL - CAS #57-55-6

*MAY NEED TO BE REGISTERED AS A TRADE SECRET

IF CAS NUMBER IS NOT AVAILABLE.

SILICA - CAS #763-18-6-9

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.