
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-180

MSDS ID: 04634

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WSM-180
PRODUCT DESCRIPTOR: PULPING ADDITIVE
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS

NONE			

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: NO
SKIN: NO
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: MAY IRRITATE EYES
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.
INGESTION: IF SWALLOWED DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: N/A IN NORMAL OPERATION

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE	DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:		LEL: NONE	UEL: NONE
UNUSUAL FIRE OR EXPLOSION HAZARDS:	NONE KNOWN		
EXTINGUISHING MEDIA:	CO2, FOAM, DRY CHEMICALS		
FIRE FIGHTING INSTRUCTIONS:	NONE		

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: FLUSH SMALL AMOUNTS TO DRAIN; COLLECT AND
RETURN LARGE AMOUNTS TO CONTAINER

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-180

MSDS ID: 04634

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: KEEP CONTAINER CLOSED. IF FROZEN, THAW AND MIX TO MAKE USABLE.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: NO
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 215 SPECIFIC GRAVITY: 1.0410
VOLATILE BY VOLUME: 45 SOLUBILITY IN WATER: 100
VAPOR PRESSURE (MMHG): 17.5 AT 20 C
APPEARANCE AND ODOR: CLEAR LIQUID; MILD ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: STRONG OXIDIZERS
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, HYDROGEN
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER, TRIPLE RINSE WITH WATER, ADD TO OPERATION. REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-180

MSDS ID: 04634

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: A

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

POLY (OXYETHYLENE/OXYPROPYLENE) GLYCOL - CAS #9003-11-6

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.