

MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-406

MSDS ID: 04636

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: WSM-406

Product Descriptor: NON-CAUSTIC PAPERMILL BOILOUT

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
DIPROPYLENE GLYCOL METHYL ETHER	34590-94-8	1 - 5%	TWA 606 STEL 909 (skin)	MG/M3
LINEAR ALCOHOL ETHOXYLATE	68439-46-3	1 - 5%	None est.	
TRIETHANOLAMINE	102-71-6	5 - 15%	TWA 5	MG/M3

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING - Contains chemicals that cause irritation to eyes and skin. May be harmful if swallowed. Wear eye protection, clothing and rubber gloves to prevent prolonged skin contact. Wash after handling.

POSSIBLE ROUTES OF ENTRY: Ingestion; Skin contact/absorption; Inhalation

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Irritation with pain, swelling and redness may develop.

SKIN: Irritation with dryness or itching may develop with pain and redness. INGESTION: If swallowed, gastric distress, diarrhea, nausea and vomiting may occur. INHALATION: May cause irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. Get medical attention.

SKIN: Flush skin with plenty of water and wash with mild soap. If irritation develops, get medical attention.

INHALATION: Remove to fresh air and seek medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NA

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: ND

UEL: ND

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-406

MSDS ID: 04636

V. FIRE FIGHTING MEASURES (Cont.)

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Not normally required.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear yellow or straw colored liquid; no odor.

BOILING POINT (DEG F): 212 F

FREEZING POINT: ND

SPECIFIC GRAVITY/BULK DENSITY: 1.1

pH: 9.5

pH 1% SOLUTION: 7.85

VOLATILE BY VOLUME: 75

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 17.5 at 20 C

VAPOR DENSITY: ND

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of sulfur; oxides of carbon; oxides of phosphorus

HAZARDOUS POLYMERIZATION: None known.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-406

MSDS ID: 04636

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: No data available.
TOXICITY TEST DATA:
No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:
No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not RCRA Regulated Hazardous Waste.
Discharge diluted product to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Rinse container with water. Recycle or dispose of container according to product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:
TSCA: All ingredients in this product are on TSCA inventory.
HAPS: Contains no hazardous air pollutants.
VOC CONTENT (EPA Method 24A): % VOC: ND Lb/Gal VOC: ND
CERCLA/EPCRA:
Section 313 Toxic Chemicals:
None
SARA Section 311/312:
ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO
SUDDEN RELEASE OF PRESSURE:NO
LISTED CARCINOGEN: NONE
NTP: NO IARC: NO OSHA: NO
HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0
PERSONAL PROTECTIVE EQUIPMENT: B
NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY:0 SPECIAL:--
STATE RIGHT-TO-KNOW INFORMATION:
LINEAR ALCOHOL ETHOXYLATE - CAS #68439-46-3
TETRASODIUM ETHYLENEDIAMINE TETRAACETATE - CAS #64-02-8
DIPROPYLENE GLYCOL METHYL ETHER - CAS #34590-94-8
WATER - CAS #7732-18-5
TRIETHANOLAMINE - CAS #102-71-6
CALIFORNIA PROPOSITION 65:
None of the ingredients are on the California proposition 65 list.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-406

MSDS ID: 04636

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.