
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

W.B. FILMITE**MSDS ID: 04651**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: W.B. FILMITE
PRODUCT DESCRIPTOR: PAINT BOOTH MASKANT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
TITANIUM DIOXIDE (13463-67-7)	<3	PEL 10, TLV 10	MG/M3

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: NO
SKIN: NO
INGESTION: NO
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: MAY IRRITATE EYES. PROLONGED OR REPEATED CONTACT MAY CAUSE
SKIN DRYNESS.
CHRONIC: SAME AS ACUTE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. IF IRRITATION DEVELOPS, GET
MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER.
INGESTION: GIVE WATER, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.
INHALATION: N/A IN NORMAL OPERATION

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE DEG F FLAME EXTENSION: N/A IN.
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: NONE UEL: NONE
UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE KNOWN
EXTINGUISHING MEDIA: CO2, FOAM, DRY CHEMICALS
FIRE FIGHTING INSTRUCTIONS: WEAR PROTECTIVE GEAR AND SELF CONTAINED
BREATHING APPARATUS IN FIRE AREA.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: FLUSH SMALL AMOUNTS TO DRAIN; COLLECT AND
RETURN LARGE AMOUNTS TO CONTAINER.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

W.B. FILMITE

MSDS ID: 04651

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: DO NOT PRESSURE CONTAINER TO EMPTY. IF FROZEN, RETURN TO PRODUCING PLANT.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: NON ABSORBENT
RESPIRATORY PROTECTION: NONE REQUIRED
OTHER PROTECTIVE CLOTHING/EQUIPMENT: CLOTHING TO PREVENT PROLONGED SKIN CONTACT.
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 215 SPECIFIC GRAVITY: 1.0400
VOLATILE BY VOLUME: 65 SOLUBILITY IN WATER: 100
VAPOR PRESSURE (MMHG): 17.5 AT 20 C
APPEARANCE AND ODOR: WHITE VISCOUS LIQUID;MILD ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: CONCENTRATED ACIDS, STRAY OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, HYDROGEN
HAZARDOUS POLYMERIZATION: NONE KNOWN

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: USE UNTIL LESS THAN ONE INCH REMAINS IN CONTAINER, EMPTY CONTAINER. TRIPLE RINSE WITH WATER, ADD TO OPERATION. REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL. CONTAINS NO PHOSPHATES.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

W.B. FILMITE

MSDS ID: 04651

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

ALL CHEMICAL INGREDIENTS ARE LISTED ON THE TSCA INVENTORY.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

POLYVINYL ACETAL - CAS #9003-33-2

WATER - CAS #7732-18-5

TITANIUM DIOXIDE - CAS #13463-67-7

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.