
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-405**MSDS ID: 04661**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WSM-405
PRODUCT DESCRIPTOR: NON-CAUSTIC PAPERMILL BOILOUT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
DIPROPYLENE GLYCOL METHYL ETHER (34590-94-8)	<10	TLV 100; PEL 100; ST 150	PPM
LINEAR ALCOHOL(C9-11) E.O. (68439-46-3)	<3	NOT ESTABLISHED	

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: NO
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: DEFATS AND IRRITATES SKIN, CAUSES SEVERE EYE IRRITATION
VAPORS IRRITATE RESPIRATORY TRACT AND CAUSE HEADACHE AND
DIZZINESS.
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER FOR AT LEAST 15 MINUTES, GET
MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER - WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES.
INGESTION: GIVE MILK OR WATER. DO NOT INDUCE VOMITING. GET MEDICAL
ATTENTION.
INHALATION: REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION.

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE	DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:		LEL: N/A	UEL: N/A
UNUSUAL FIRE OR EXPLOSION HAZARDS:		NONE KNOWN	
EXTINGUISHING MEDIA:		FOAM, CO2, DRY CHEMICAL	
FIRE FIGHTING INSTRUCTIONS:		NONE	

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-405**MSDS ID: 04661**

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: FLUSH SMALL AMOUNTS TO DRAIN, COLLECT AND RETURN LARGE AMOUNTS TO CONTAINER.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: KEEP CONTAINER CLOSED WHEN NOT IN USE. IF FROZEN, THAW AND MIX TO MAKE USABLE.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD
PROTECTIVE GLOVES: SOLVENT RESISTANT
RESPIRATORY PROTECTION: USE NIOSH APPROVED RESPIRATOR IF TLV/PEL LIMIT EXCEEDED.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: WEAR APRON WHEN HANDLING
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 212 SPECIFIC GRAVITY: 1.0470
VOLATILE BY VOLUME: <85 SOLUBILITY IN WATER: 100
VAPOR PRESSURE (MMHG): 17.5 AT 20 C
APPEARANCE AND ODOR: CLEAR, LIGHT-YELLOW LIQUID

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: CONCENTRATED ACIDS, AVOID MIXING WITH NITRITES.
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON
HAZARDOUS POLYMERIZATION: NONE KNOWN

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: PH ADJUSTMENT. USE UNTIL LESS THAN ONE INCH REMAINS IN CONTAINER, EMPTY CONTAINER. TRIPLE RINSE WITH WATER, ADD TO OPERATION. REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-405

MSDS ID: 04661

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

TETRAPOTASSIUM PYROPHOSPHATE - CAS #7320-34-5

WATER - CAS #7732-18-5

TRIETHANOLAMINE - CAS #102-71-6

DIPROPYLENE GLYCOL METHYL ETHER - CAS #34590-94-8

LINEAR ALCOHOL(C9-11) ETHOXYLATED - CAS #68429-46-3

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.