
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-187**MSDS ID: 04720**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: WSM-187

Product Descriptor: PAPER MILL DEFOAMER

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
----------------	------------	---	-----------------	-------

NONE

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING - Product contains irritating or harmful chemicals which cause eye or skin irritation or burns. May be harmful if swallowed. Do not get product in eyes, on skin or clothing. Wear eye protection and rubber gloves to prevent skin contact when handling product. Wash after handling. Avoid breathing dust, vapors or product spray.

POSSIBLE ROUTES OF ENTRY: Ingestion; Skin contact/absorption; Inhalation**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

ACUTE: EYES: Burns or severe irritation with pain, redness and swelling.
SKIN: Severe irritation or burns with rash, redness, pain or itching. **INGESTION:** If swallowed, pain, nausea and vomiting may result. **INHALATION:** Causes irritation of respiratory tract.

CHRONIC: Same as acute effects.**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** Dermatitis or sensitive skin.**TARGET ORGAN(S) OF CHEMICAL HAZARD(S):** Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.**SKIN:** Flush thoroughly with plenty of water. Wash with mild soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.**INGESTION:** If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. **NOTE:** Never give fluids by mouth to an unconscious person.**INHALATION:** Remove to fresh air and seek medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-187

MSDS ID: 04720

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): >300 FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: ND UEL: ND
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists.
PROTECTIVE GLOVES: Acid resistant.
RESPIRATORY PROTECTION: Not normally required.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Chemical apron.
ENGINEERING CONTROLS:
VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear amber liquid; fatty odor.

BOILING POINT (DEG F): 212 F	FREEZING POINT: ND
SPECIFIC GRAVITY/BULK DENSITY: .983	
pH: 3	pH 1% SOLUTION: 7.48
VOLATILE BY VOLUME: 5	
SOLUBILITY IN WATER: Soluble	
VAPOR PRESSURE(mmHg): 17.5 at 20 C	VAPOR DENSITY: ND

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-187

MSDS ID: 04720

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents; Chlorine and chlorinated compounds; Alkalies

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of carbon

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: No data available.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not RCRA Regulated.

Discharge diluted product to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Rinse container with water. Recycle or dispose of container according to product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: ND Lb/Gal VOC: ND

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: C

NFPA RATING: HEALTH: 1 FIRE: 0 REACTIVITY: 0 SPECIAL: ---

STATE RIGHT-TO-KNOW INFORMATION:

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-187

MSDS ID: 04720

XV. REGULATORY INFORMATION (Cont.)

WATER - CAS #7732-18-5
PROPRIETARY NONIONIC SURFACTANT MIXTURE.
CALIFORNIA PROPOSITION 65:
None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.