

CONFIDENCE 40 C

MSDS ID: 04882

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: CONFIDENCE 40C

Product Descriptor: BOILER ADDITIVE (SOFT WATER)

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
DIETHYLAMINO ETHANOL	100-37-8	5 - 15%	TWA 10 (skin)	PPM
POTASSIUM HYDROXIDE	1310-58-3	1 - 5%	TWA - C 2	MG/M3
POTASSIUM SULFITE	10117-38-7	5 - 15%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe irritation with redness, pain and swelling. SKIN: Irritation with dryness or itching may develop with pain and redness. INGESTION: If swallowed in large amounts, systemic poisoning may result with respiratory, circulatory and central nervous system (CNS) depression. INHALATION: Dust, spray or mists may cause burns or irritation.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush skin with plenty of water and wash with mild soap. If irritation develops, get medical attention.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air and seek medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/14/03
Printed 2/03/04

CONFIDENCE 40 C

MSDS ID: 04882

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: NONE UEL: NONE
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Flush small amounts to drain. Collect and return large amounts to container.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists.
PROTECTIVE GLOVES: Alkali resistant.
RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Chemical apron.
ENGINEERING CONTROLS:
VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Amber liquid, mild organic odor.

BOILING POINT (DEG F): 220	FREEZING POINT: 22 F
SPECIFIC GRAVITY/BULK DENSITY: 1.12	
pH: 10.5	pH 1% SOLUTION: 10.3
VOLATILE BY VOLUME: 65	
SOLUBILITY IN WATER: Miscible	
VAPOR PRESSURE(mmHg): 17.5 at 20 C	VAPOR DENSITY: 17.3

CONFIDENCE 40 C

MSDS ID: 04882

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of carbon; oxides of nitrogen; oxides of sulfur

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

TOXICITY TEST DATA:

Potassium Hydroxide:

Acute Oral LD50 (rat) - 365 mg/kg (RTECS)

Acute Skin LD50 (rabbit) - 1260 mg/kg (MSI)

Diethylamino ethanol:

Intraperitoneal LD50 (rat) 1220 mg/kg

Dermal LD50 (rabbit) 1260 mg/kg

Dermal LD50 (Guinea pig) 1000 mg/kg

Oral LD50 (rat) 1300 mg/kg

Intraperitoneal LD50 (mouse) 1561 mg/kg

Intramuscular LD50 (mouse) 416 mg/kg

Subcutaneous LD50 (mouse) 308 mg/kg

XII. ECOLOGICAL INFORMATION

Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

ECOTOXICITY TEST DATA:

Potassium Hydroxide:

Acute LC50 (96 hr.) (Pimephles promelas) - 179 mg/l

Acute LC50 (96 hr.) (Daphnia magna) - 60 mg/l

Diethylamino Ethanol:

LC50 (96 hr) (Pimephales promelas) 1780 mg/l

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Adjust pH of diluted product and discharge to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container according to product labeling or Federal, State or local regulations.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/14/03
Printed 2/03/04

CONFIDENCE 40 C

MSDS ID: 04882

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: NONE

VOC CONTENT (EPA Method 24A): % VOC: 10 Lb/Gal VOC: 0.93

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: C

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY: 0 SPECIAL: IRRITANT

STATE RIGHT-TO-KNOW INFORMATION:

DIETHYLAMINO ETHANOL - CAS #100-37-8

WATER - CAS #7732-18-5

SODIUM SULFITE - CAS #7757-83-7

POTASSIUM SULFITE - CAS #10117-38-1

POTASSIUM HYDROXIDE - CAS #1310-58-3

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.