



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 0506

PRODUCT NAME: ALL BRITE**USE:** Stainless Steel/Aluminum Truck Brightener**SUPPLIER:**JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada**EMERGENCY PHONE:****1-800-668-7171****WHMIS CLASSIFICATION:** D1A E**CHEMICAL FAMILY:** Mineral Acid**TRADE NAME / SYNONYMS:** not applicable**CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Sulphuric acid	7-13	007664-93-9	LD50 2140 mg/kg	oral/rat
Hydrofluoric acid	7-13	007664-39-3	LC50 638 ppm/4H	inh/rat
Sodium alphaolefin sulphonate	1-5	068439-57-6	LD50 3500 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:**Gloves:** Natural Rubber or Neoprene**Eye:** safety goggles**Footwear:** rubber boots**Respiratory:** face mask with NIOSH approved cartridge for
Acid Mist**Other:** rubber apron or suit, face shield**SPECIAL HANDLING PROCEDURES AND EQUIPMENT:**

Do not breathe mist, spray or vapour. When spraying, wear NIOSH approved respirator for acid mist. Avoid eye and skin contact. Do not allow contact with glass or ceramic materials.

VENTILATION REQUIREMENTS: Mechanical exhaust. Wear NIOSH approved respirator for acid mist.**INCOMPATIBILITY (Material to Avoid):** Alkaline or chlorinated materials.**SPILL PROCEDURES:** Contain the spill. Do not allow the spilled product to go to drain. SMALL SPILLS: Neutralize with mild alkaline solution and soak up with absorbent clay for disposal. LARGE SPILLS: Flush to holding tank and neutralize with mild alkaline material before disposal.**WASTE DISPOSAL:** Dispose according to municipal, provincial, and federal regulations.**STORAGE / SHIPPING REQUIREMENT:** Store in a cool dry area in a closed container. Avoid freezing. UN1786

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, colourless liquid**S.G. / BULK DENSITY(g/cc):** 1.11**pH:** (concentrate): < 1.5**VAPOUR PRESSURE (mmHg):** not available**VAPOUR DENSITY (air=1):** not available**ODOUR THRESHOLD:** not available**BOILING POINT:** approx. 100°C**FREEZING POINT:** approx. 0°C**PERCENT VOLATILE:** 70%**SOLUBILITY IN WATER:** Soluble**EVAPORATION RATE (water=1):** not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**EYES:** Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.**SKIN:** Corrosive. May cause severe irritation. Contains hydrofluoric acid. May cause ulcerations of the skin and possible fluoride absorption if not treated promptly.

INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause permanent damage if not treated promptly.	
INHALATION: Inhalation of spray or mist may cause severe respiratory irritation. See "Other Toxic Effects"	
LD50 (calculated): 2140 mg/kg	LC50 (calculated): 638 ppm/4hr.
OTHER TOXIC EFFECTS: TLV-TWA 1 mg/m3 as Sulphuric Acid, STEL 3 mg/m3. IARC has classified "occupational exposure to strong acid mists containing sulphuric acid" as being carcinogenic to humans. The route of entry is inhalation of these mists resulting in respiratory (Laryngeal) cancers. There is no evidence that the liquid is in any way a carcinogen.	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: None known.	
VI - FIRST AID MEASURES	
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.	
SKIN: Flush affected area thoroughly with water. Obtain medical attention immediately. Should this be delayed, apply magnesia paste (magnesium/oxide/glycerine) or milk of magnesia.	
INGESTION: Drink large volumes of water. Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.	
INHALATION: Remove patient to fresh air. Contact a physician.	
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: not applicable	
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus.	
HAZARDOUS COMBUSTION PRODUCTS: Hydrogen fluoride. Oxides of carbon, sulphur.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: keep from freezing	
INCOMPATIBILITY (Material to Avoid) : Alkaline or chlorinated compounds. Heat and/or toxic gases generated upon contact. Do not allow contact with glass and ceramic materials.	
HAZARDOUS DECOMPOSITION PRODUCTS: Hydrogen, sulphur dioxide, sulphur trioxide, hydrogen fluoride	
REACTIVITY: Not dangerously reactive.	
IX - MSDS PREPARATION	
SOURCES USED: RTECS, ChemInfo	PREPARED BY: JohnsonDiversey Canada. Inc. Regulatory Department Industrial Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	