

MATERIAL SAFETY DATA SHEET



MSDS ID: 2918430



I - PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: TAR AND ASPHALT CLEANER 150

USE: Tar and asphalt cleaner

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc.

2401 Bristol Circle **1-800-668-7171**Oakville Ontario, L6H 6P1, Canada

WHMIS CLASSIFICATION: B3 D2B E TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: surfactant caustic alkali CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Cyclohexanol	3-7	000108-93-0	LD50 2060 mg/kg	oral/rat
Alcohol ethoxylated	3-7	068002-97-1	LD50 2750 mg/kg	oral/rat
Potassium hydroxide	0.5- 1.5	001310-58-3	LD50 273 mg/kg	oral/rat
Naphtha petroleum	30-60	064742-94-8	LD50 3000 mg/kg	oral/rat
Sodium dodecylbenzene sulphonate	3-7	025155-30-0	LD50 1260 mg/kg	oral/rat
Pine oil	3-7	008002-09-3	LD50 3200mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Impermeable gloves Eye: Safety goggles Footwear: Not required

Respiratory: If mists are generated, use NIOSH approved **Other:** Not required

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Do not breathe mist, spray or vapours . Avoid eye and skin contact.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): Strong oxidizers

SPILL PROCEDURES: Wear protective clothing. Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with

absorbent clay for disposal.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations. Wash spill area with large volumes of water.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN3266

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear amber liquid

S.G. / BULK DENSITY(g/ce): 0.95 **pH:** (Conc.) 12.7 - 13.5

VAPOUR PRESSURE (mmHg):not availableVAPOUR DENSITY (air=1):not applicable

ODOUR THRESHOLD: not available BOILING POINT: approx. 100°C

FREEZING POINT: -4°C PERCENT VOLATILE: 75%

SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): less than 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation.

INGESTION: Harmful or fatal if swallowed. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not

INHALATION: Breathing spray or mist may cause respiratory irritation. Aspiration into the lungs may cause chemical pneumonitis.

LD50 (calculated): 3300 mg/kg. LC50 (calculated): Not available

OTHER TOXIC EFFECTS: None known.

EFFECTS OF CHRONIC None known.

EXPOSURE TO MATERIAL:

VI - FIRST AID MEASURES

EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.

SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.

INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a

physician immediately.

INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.

VII - FIRE AND EXPLOSION DATA

FLAMMABLE: Yes, combustible if heated.

FLASH POINT, °C: 68°C (Pensky-Martens) **AUTO IGNITION TEMPERATURE,°C:** N/A

EXTINGUISHING MEDIA: Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other []

SPECIAL FIRE FIGHTING PROCEDURES: Use water to extinguish only if large volumes are available to flood area.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.

EXPLOSIVE SENSITIVITY TO: not applicable

VIII - REACTIVITY DATA

STABILITY: Unstable [] Stable [X]

CONDITIONS TO AVOID: high temperature

INCOMPATIBILITY (Material to Avoid): Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide

REACTIVITY: not dangerously reactive.

IX - MSDS PREPARATION

SOURCES USED: **RTECS** PREPARED BY: JohnsonDiversey Canada, Inc.

Regulatory Department Industrial Division PREPARATION DATE: April 15, 2003 Phone (905) 829-1200

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.