
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 10/21/03
Printed 2/03/04

ISC-24A**MSDS ID: 05241**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: ISC-24A

Product Descriptor: SOLVENT-EMULSIFIER

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
ALCOHOLS ETHOXYLATED	68002-97-1	1 - 5%	None established	
AROMATIC PETROLEUM DISTILLATE	64742-94-5	>30%	PEL 100 LV 5	TPPM MG/M3
CYCLOHEXANOL	108-93-0	5 - 15%	TWA 206 (skin)	MG/M3
POTASSIUM HYDROXIDE	1310-58-3	< 1.0 %	TWA - C 2	MG/M3

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE MATERIAL - Causes severe burns to skin and eyes. Harmful if swallowed. Do not contact eyes, skin or clothing. Avoid breathing any dust, spray mist or vapors in spill area. Wash thoroughly after handling product. Wear eye protection, clothing and footwear to prevent skin contact.
POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Irritation with pain, swelling and redness may develop.
SKIN: Irritation with dryness or itching may develop with pain and redness. **INGESTION:** If swallowed, gastric distress, diarrhea, nausea or vomiting may occur. If vomiting occurs, petroleum distillates may be inhaled into the lungs and cause chemical pneumonia. **INHALATION:** Overexposure to vapors may cause dizziness, headache, fatigue and respiratory irritation.

CHRONIC: (Petroleum Distillates) Asthma or reactive airway disease.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin, respiratory tract, and gastrointestinal tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids apart to completely flush all chemicals from entire eye surface. Get immediate medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with mild soap and water. Remove contaminated clothes and shoes and clean before

ISC-24A

MSDS ID: 05241

IV. FIRST AID MEASURES (Cont.)

reuse. Get medical attention for any painful, red or injured skin.

INGESTION: Contains petroleum distillates. Do not induce vomiting because of aspiration hazard. Do not give liquids by mouth except by order of a physician. Contact a physician or Poison Control Center.

INHALATION: If inhaled, move to fresh air. If patient is not breathing, give artificial respiration. If breathing is difficult, give oxygen under the direction of trained personnel or a physician. Get immediate medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): 150 FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/D UEL: N/D

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: COMBUSTIBLE. Avoid sparks or open flames. Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Turn off sources of ignition. Contain the spill. Prevent spill from entering sewer. Recover free liquid and/or collect with inert oil absorbent. Place absorbent into metal container for disposal. Clean spill area with detergent or solvent cleaner. Dispose of waste in accordance with local State and Federal regulations.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: COMBUSTIBLE PRODUCT. Do not store near heat, sparks or open flames. Keep container closed when not in use. Product may accumulate a static charge. Use proper grounding during storage or emptying container. Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists. Face shields.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots and chemical resistant apron

ISC-24A

MSDS ID: 05241

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION (Cont.)

if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear, amber liquid, aromatic solvent odor (pine).

BOILING POINT (DEG F): 400

FREEZING POINT: <50 F

SPECIFIC GRAVITY/BULK DENSITY: 0.9500

pH: 12.7-13.5

pH 1% SOLUTION: N/D

VOLATILE BY VOLUME: 77.6

SOLUBILITY IN WATER: Partially Soluble

VAPOR PRESSURE(mmHg): 1.0 at 20 C

VAPOR DENSITY: 4

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of sulfur; oxides of carbon

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

TOXICITY TEST DATA:

Potassium Hydroxide:

Acute Oral LD50 (rat) - 365 mg/kg (RTECS)

Acute Skin LD50 (rabbit) - 1260 mg/kg (MSI)

ALCOHOL ETHOXYLATE:

Acute Oral LD50 (rat) - 3.2 gm/kg

Acute Dermal LD50 (rabbit) - 72 gm/kg

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: CONCENTRATED PRODUCT WOULD BE CONSIDERED D002-CORROSIVE, IF DECLARED HAZARDOUS WASTE.

Spent or excess product is hazardous waste. Do not discharge to sewer or environment. Arrange disposal through a licensed disposal company or treat by special Waste Disposal Sheet. Recycle or dispose of containers by product

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 10/21/03
Printed 2/03/04

ISC-24A

MSDS ID: 05241

XIII. DISPOSAL CONSIDERATIONS (Cont.)

labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: NONE

VOC CONTENT (EPA Method 24A): % VOC: 50 Lb/Gal VOC: 3.98

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

THIS PRODUCT CONTAINS CYCLOHEXANOL

(CAS# 108-93-6) AT 6%, WHICH IS SARA REPORTABLE.

SARA Section 311/312:

ACUTE:YES CHRONIC:NO FIRE:YES REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: NONE

NTP: NO

IARC: NO

OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 2 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 2 REACTIVITY:0 SPECIAL:CORROSIVE

STATE RIGHT-TO-KNOW INFORMATION:

PETROLEUM NAPHTHA - CAS #64742-94-5

CYCLOHEXANOL - CAS #108-93-0

POTASSIUM HYDROXIDE - CAS #1310-58-3

LINEAR ALCOHOL ETHOXYLATE - CAS# 68439-46-3

WATER - CAS# 7732-18-5

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.