

# MATERIAL SAFETY DATA SHEET



MSDS ID: 0525



I - PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: SUPER SHEEN LP

**USE:** Acid Cleaner

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: D1A E TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: mineral acid CHEMICAL NAME: not applicable

#### **II - HAZARDOUS INGREDIENTS**

| HAZARDOUS INGREDIENT | % w/w | CAS#        | LD50 / LC50     | Route / Species |
|----------------------|-------|-------------|-----------------|-----------------|
| Nitric acid          | 15-40 | 007697-37-2 | LC50 49 ppm/4H  | inh/rat         |
| Phosphoric acid      | 5-10  | 007664-38-2 | LD50 1530 mg/kg | oral/rat        |

## **III - HANDLING AND DISPOSAL PROCEDURES**

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Neoprene or Nitrile Eye: safety goggles Footwear: not required

**Respiratory:** If mists are generated, use NIOSH approved **Other:** rubber apron

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Do not breathe mist, spray or vapours. Avoid eye and skin contact.

**VENTILATION REQUIREMENTS:** mechanical exhaust.

**INCOMPATIBILITY (Material to Avoid):** Alkaline and chlorinated materials. Organic materials.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN1760

## **IV - PHYSICAL PROPERTIES**

APPEARANCE / ODOUR: Clear, colourless liquid

**S.G. / BULK DENSITY(g/cc):** 1.25 **pH:** (4% solution): 1.2

VAPOUR PRESSURE (mmHg): not applicable VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not available BOILING POINT: 100°C

FREEZING POINT: not available PERCENT VOLATILE: 90%

SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): not applicable

#### **V - TOXICOLOGICAL PROPERTIES**

**EFFECTS OF ACUTE EXPOSURE TO MATERIAL:** 

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly.

**INHALATION:** May cause irritation of respiratory tract.

LD50 (calculated): not available LC50 (calculated): 49 ppm/4 hr.

OTHER TOXIC EFFECTS: Breathing vapours may cause delayed lung injury. TLV: (Nitric acid): TWA 2 ppm (~5mg/m3), STEL 4 ppm (~10

mg/m3):

(Phosphoric acid): TWA 1 mg/m3, STEL 3 mg/m3

EFFECTS OF CHRONIC

not available

**EXPOSURE TO MATERIAL:** 

#### **VI - FIRST AID MEASURES**

EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.

**SKIN:** Flush affected area thoroughly with water. If irritation develops, contact a physician.

INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a

physician immediately.

INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.

#### VII - FIRE AND EXPLOSION DATA

FLAMMABLE: Contact with metals forms flammable hydrogen gas.

FLASH POINT, °C: not applicable AUTO IGNITION TEMPERATURE, °C: N/Ap

**EXTINGUISHING MEDIA:** Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.

HAZARDOUS COMBUSTION PRODUCTS: not applicable.

**EXPLOSIVE SENSITIVITY TO:** not applicable

#### **VIII - REACTIVITY DATA**

STABILITY: Stable [x] Unstable []

**CONDITIONS TO AVOID:** not applicable.

**INCOMPATIBILITY (Material to Avoid):** Alkaline and chlorinated materials. Aluminium, brass, copper, iron, mild steel. Organic materials.

**HAZARDOUS DECOMPOSITION PRODUCTS:** 

Contact with chlorinated materials will release chlorine gas. Contact with alkali will generate heat. Contact with soft metals forms flammable hydrogen gas. Contact with organic

materials will generate heat.

**REACTIVITY:** not dangerously reactive

# **IX - MSDS PREPARATION**

SOURCES USED: RTECS, Industrial Chemicals Safety Manual PREPARED BY: JohnsonDiversey Canada, Inc.

Regulatory Department

PREPARATION DATE: April 15, 2003 Food Division

Phone (905) 829-1200

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.