



## **MATERIAL SAFETY DATA SHEET**



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 0586						
PRODUCT NAME: DESCALER D53						
USE: Acid Descaler						
SUPPLIER: JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada		EMERGENCY PHONE: 1-800-668-7171				
WHMIS CLASSIFICATION:       D1A       E         CHEMICAL FAMILY:       mineral acid		TRADE NAME / SYNONYMS:       not applicable         CHEMICAL NAME:       not applicable				
II - HAZARDOUS INGREDIENTS						
HAZARDOUS INGREDIENT	% w/w	1	CAS #	LD50 / LC50	Route / Species	
Nitric acid Phosphoric acid	10-30 15-40		007697-37-2 007664-38-2	LC50 49 ppm/4H LD50 1530 mg/kg	inh/rat oral/rat	
III - HANDLING AND DISPOSAL PROCEDURES						
PERSONAL PROTECTIVE EQUIPMENT:         Gloves:       neoprene or nitrile       Eye:       safety goggles       Footwear:       not required         Respiratory:       If mists are generated, use NIOSH approved mask       Other:       rubber apron         SPECIAL HANDLING PROCEDURES AND EQUIPMENT:       Avoid eye and skin contact. Do not breathe mist, spray or vapours.         VENTILATION REQUIREMENTS:       Local exhaust ventilation.         INCOMPATIBILITY (Material to Avoid):       Alkaline and chlorinated materials.         SPILL PROCEDURES:       Contain the spill. Do not allow the spilled product to go to drain. Neutralize with sodium bicarbonate, sodium carbonate or lime. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.         WASTE DISPOSAL:       Dispose according to municipal, provincial, and federal regulations.       Store in a cool dry area in a closed container.       UN3264						
IV - PHYSICAL PROPERTIES						
APPEARANCE / ODOUR: Clear, colourless liquid						
S.G. / BULK DENSITY(g/cc): 1.26		pH: (concentrate): < 1.0 VAPOUR DENSITY (air=1): not available				
VAPOUR PRESSURE (mmHg):       not available         ODOUR THRESHOLD:       not available		BOILING POINT: 100°C				
FREEZING POINT: not available		PERCENT VOLATILE: 60%				
SOLUBILITY IN WATER: soluble		EVAPORATION RATE (water=1): approx. 1				
V - TOXICOLOGICAL PROPERTIES						
EFFECTS OF ACUTE EXPOSURE TO MATERIAL:         EYES:       Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.         SKIN:       Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.         INGESTION:       Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly.         INHALATION:       Corrosive. Inhalation of spray or mist may cause severe respiratory irritation.						
LD50 (calculated): not available			(calculated): 49	ppm/4 hr.		

OTHER TOXIC EFFECTS: Breathing vapours may cause delayed lung injury. TLV (nitric acid) - TWA 2 ppm, - STEL 4 ppm; TLV (phosphoric acid) - TWA 1 mg/m3, - STEL 3 mg/m3						
EFFECTS OF CHRONIC not available EXPOSURE TO MATERIAL:						
VI - FIRST AID MEASURES						
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.						
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.						
<b>INGESTION:</b> Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.						
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.						
VII - FIRE AND EXPLOSION DATA						
FLAMMABLE: No. Contact with metals forms flammable hydrogen gas						
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE,°C: N/Ap					
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []						
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.						
HAZARDOUS COMBUSTION PRODUCTS: not applicable.						
EXPLOSIVE SENSITIVITY TO: not applicable						
VIII - REACTIVITY DATA						
STABILITY: Stable [x] Unstable [ ]						
CONDITIONS TO AVOID: Contact with soft metals.						
<b>INCOMPATIBILITY (Material to Avoid) :</b> Alkaline and chlorinated materials. Aluminium, brass, copper, iron, mild steel. Organic materials.						
HAZARDOUS DECOMPOSITION PRODUCTS: Contact with chlorinated materials will release chlorine gas. Contact with alkali will generate heat. Contact with soft metals forms flammable hydrogen gas. Contact with organic materials will generate heat.						
REACTIVITY: not dangerously reactive						
IX - MSDS PREPARATION						
SOURCES USED: RTECS	PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department					
PREPARATION DATE: April 15, 2003	Institutional Division Phone (905) 829-1200					
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.						