
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUJET EDS

MSDS ID: 06204

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Product Discriptor:

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
DUJET EDS		>30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: CAUSES BURNS TO SKIN AND EYES. MISTS ARE CORROSIVE TO RESPIRATORY TRACT.

CHRONIC: SAME AS ACUTE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Sensitive skin

IV. FIRST AID MEASURES

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: NONE

UEL: NONE

EXTINGUISHING MEDIA: CO2, FOAM, DRY CHEMICALS

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

FLUSH SMALL AMOUNTS TO DRAIN; COLLECT AND RETURN LARGE AMOUNTS TO DRUM.

REPORTABLE QUANTITY (R.Q.) OF PRODUCT: 25,806 LBS. OR 2,900 GAL.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: IF FROZEN, THAW AND MIX TO MAKE USABLE. KEEP BUNGS IN DRUM. KEEP FROM FREEZING. DO NOT PRESSURE TO EMPTY CONTAINER.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUJET EDS

MSDS ID: 06204

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD
PROTECTIVE GLOVES: ALKALI RESISATANT
OTHER PROTECTIVE CLOTHING/EQUIPMENT: BOOTS AND APRON WHEN STEAM CLEANING, WITH ADEQUATE VENTILATION.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: PRODUCE NORMAL AIR DILUTION
LOCAL VENTILATION: NO

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

BOILING POINT (DEG F): 220	FREEZING POINT: Not determined
SPECIFIC GRAVITY/BULK DENSITY:	
pH:	pH 1% SOLUTION: Not Determined
VOLATILE BY VOLUME: 80	
VAPOR PRESSURE(mmHg): 17.5 at 20 C	VAPOR DENSITY: N/A

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: CO, WITH INCOMPLETE COMBUSTION
HAZARDOUS DECOMPOSITION PRODUCTS: None known.
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

No data available.
TOXICITY TEST DATA:
No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA: No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.
USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER TRIPLE RINSE WITH WATER, DISPOSE TO INDUSTRIAL OR SANITARY SEWER REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUJET EDS**MSDS ID: 06204**

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: Lb/Gal VOC:

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: FIRE: REACTIVITY: SPECIAL:

STATE RIGHT-TO-KNOW INFORMATION:

POTASSIUM HYDROXIDE - CAS #1310-58-3

POLY(OXY-1,2-ETHANEDIYL),ALPHA-(NONYLPHENYL)-OMEGA-HYDROXY -

CAS #9016-45-9

WATER - CAS #7732-18-5

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.