

SAF-T-BRITE II

MSDS ID: 06495

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: SAF-T-BRITE II
Product Descriptor: General Purpose Cleaner
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
D-LIMONENE	5989-27-5	1 - 5%	None Established	
LINEAR ALCOHOL ETHOXYLATE	68439-46-3	1 - 5%	None est.	
SODIUM METASILICATE	6834-92-0	< 1.0 %	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING - Product contains irritating or harmful chemicals which cause eye or skin irritation or burns. May be harmful if swallowed. Do not get product in eyes, on skin or clothing. Wear eye protection and rubber gloves to prevent skin contact when handling product. Wash after handling. Avoid breathing dust, vapors or product spray.

POSSIBLE ROUTES OF ENTRY: All Routes of Entry/Exposure

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe irritation with redness, pain and swelling. SKIN: Irritation with dryness or itching may develop with pain and redness. INGESTION: If swallowed, gastric distress, diarrhea, nausea and vomiting may occur. INHALATION: Causes irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush skin with plenty of water and wash with mild soap. If irritation develops, get medical attention.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air and seek medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SAF-T-BRITE II**MSDS ID: 06495**

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): 133 FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: ND UEL: ND
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: OSHA Combustible due to flashpoint, but product does not sustain combustion after flashing. Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Turn off sources of ignition. Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: COMBUSTIBLE PRODUCT. Do not store near heat, sparks or open flames. Keep container closed when not in use. Product may accumulate a static charge. Use proper grounding during storage or emptying container. Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Face shields.
PROTECTIVE GLOVES: Alkali resistant.
RESPIRATORY PROTECTION: Use NIOSH/MSHA approved respirator where TLV/PEL may be exceeded.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots and chemical resistant apron if contact or splash hazard exists.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Good general ventilation should be sufficient to control airborne levels.
LOCAL VENTILATION: Use explosion-proof ventilation equipment for vapors or fumes.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear yellow liquid with slight citrus odor.

BOILING POINT (DEG F): 220
SPECIFIC GRAVITY/BULK DENSITY: 1.034
pH: 12.9

FREEZING POINT: 0 C
pH 1% SOLUTION: 10.6

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SAF-T-BRITE II**MSDS ID: 06495**

IX. PHYSICAL AND CHEMICAL PROPERTIES (Cont.)

VOLATILE BY VOLUME: 87.5
SOLUBILITY IN WATER: Soluble
VAPOR PRESSURE(mmHg): 17.5 at 20 C VAPOR DENSITY: 17.3

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.
INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of sulfur; oxides of carbon
HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

TOXICITY TEST DATA:**Sodium Hydroxide:**

Acute Oral LD50 (rat) 500 mg/kg (RTECS)
Acute Skin LD50 (rabbit) 1350 mg/kg (MSI)

Alcohol Ethoxylates (CAS# 68439-46-3):

Acute Oral LD50 (rat) 1.4 gm/kg
Acute Dermal LD50 (rabbit) 5 gm/kg
Eye Irritation (rabbit) Severe
Skin Irritation (rabbit) Draize 1.2 (4 hrs.)

D-Limonene:

Acute Oral LD50 (rat) >5 gm/kg
Acute Dermal LD50 (rabbit) >5 gm/kg
Eye Irritation: severe
Skin Irritation: severe

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

ECOTOXICITY TEST DATA: ETHYLENE DIAMINE TETRAACETIC ACID: Acute
LC50 (Lepomis macrochirus)- 550 mg/l
Acute LC50 (Daphnia magna) - 595 mg/l

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Product is considered D002 - Corrosive if declared Hazardous Waste.

Spent or excess product is hazardous waste. Do not discharge to sewer or environment. Arrange disposal through a licensed disposal company or treat by special Waste Disposal Sheet. Recycle or dispose of containers by product labeling or governmental regulations.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SAF-T-BRITE II**MSDS ID: 06495**

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: NONE

VOC CONTENT (EPA Method 24A): % VOC: 5% Lb/Gal VOC: 0.432

CERCLA/EPCRA:

Section 313 Toxic Chemicals: NONE

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: YES REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 2 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 2 FIRE: 2 REACTIVITY: 0 SPECIAL: ALKALINE

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

LINEAR ALCOHOL ETHOXYLATE - CAS #68439-46-3

SODIUM DODECYLBENZENE SULFONATE - CAS #25155-30-0

SODIUM METASILICATE - CAS #6834-92-0

D-LIMONENE - CAS #5989-27-5

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.