
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD CRYSTALITE CROSS-LINKED**MSDS ID: 07617**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: OXFORD CRYSTALITE CROSS-LINKED
PRODUCT DESCRIPTOR: SYNTHETIC FLOOR FINISH
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
DIETHYLENE GLYCOL METHYL ETHER (111-77-3)	2	NONE ESTABLISHED	
DIETHYLENE GLYCOL ETHYL ETHER (111-90-0)	2	NONE ESTABLISHED	
DIBUTYLPHTHALATE (84-74-2)	1	TLV 5; PEL 5	MG/M3
NON-HAZARDOUS: WATER (7732-18-5) ACRYLIC COPOLYMER			

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: NO
SKIN: NO
INGESTION: NO
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION.
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.
SKIN: FLUSH WITH PLENTY OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.
INGESTION: INDUCE VOMITING BY ADMINISTERING SYRUP OF IPECAC, U.S.P. SOAPY WATER OR BY STICKING FINGER DOWN THROAT. REPEAT UNTIL VOMIT IS CLEAR. GET IMMEDIATE MEDICAL ATTENTION.
INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION.

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE	DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:		LEL: N/K	UEL: N/K
UNUSUAL FIRE OR EXPLOSION HAZARDS:		NONE KNOWN	
EXTINGUISHING MEDIA:		WATER	

OXFORD CRYSTALITE CROSS-LINKED

MSDS ID: 07617

V. FIRE FIGHTING MEASURES (Cont.)

FIRE FIGHTING INSTRUCTIONS: NONE

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: MOP UP SMALL SPILLS INTO BUCKET OF WATER. DIKE AREA TO CONTAIN LARGE SPILLS; PUMP LIQUID TO SUITABLE CONTAINER. PICK UP RESIDUE ON ABSORBENT MATERIAL AND TRANSPORT TO AUTHORIZED HAZARDOUS CHEMICAL WASTE TREATMENT FACILITY. FLUSH AREA TO SANITARY SEWER SYSTEM WITH WATER.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: KEEP FROM FREEZING. STORE IN COOL, DRY LOCATION. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. DO NOT POUR USED PRODUCT FROM MOP BUCKET BACK INTO CONTAINER.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: RUBBER GLOVES IF PROLONGED OR REPEATED CONTACT IS LIKELY
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 212 SPECIFIC GRAVITY: 1.0200
VOLATILE BY VOLUME: 4 SOLUBILITY IN WATER: LOW
VAPOR PRESSURE (MMHG): 17.5 AT 20 C
APPEARANCE AND ODOR: THIN, OFF-WHITE, MILKY EMULSION; MILD ACRYLIC ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: ACIDS, OXIDIZING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS: CO₂, CARBON MONOXIDE
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

OXFORD CRYSTALITE CROSS-LINKED

MSDS ID: 07617

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: TRIPLE RINSE CONTAINER WITH COLD WATER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

THIS PRODUCT CONTAINS DIETHYLENE GLYCOL METHYL ETHER, CAS #111-77-3, AT 2%; DIETHYLENE GLYCOL ETHYLETHER, CAS #111-90-0, AT 2%; AND DIBUTYLPHTHALATE, CAS #84-74-2, AT 1% IN THE FORMULATION. THESE INGREDIENTS ARE SARA REPORTABLE.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

N/A

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.