
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD SUPER KLEEN**MSDS ID: 07657**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Product Descriptor:

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800) 851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
OXFORD SUPER KLEEN		>30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: PRODUCT AND SOLUTIONS OF PRODUCT WILL CAUSE IMMEDIATE DESTRUCTION OF EYE TISSUE UPON CONTACT. CORROSIVE TO SKIN AND EYES. HARMFUL OR FATAL IF SWALLOWED.

CHRONIC: SAME AS ACUTE

IV. FIRST AID MEASURES

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA: WATER USED IN LARGE VOLUMES, FOAM, DRY CHEMICAL

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

FLUSH SMALL SPILL TO SANITARY SEWER SYSTEM WITH LARGE VOLUME OF COLD WATER. PROVIDE PROTECTIVE CLOTHING FOR LARGE SPILL CLEANUP. SWEEP UP AND SHOVEL INTO INTACT CONTAINER AND TRANSPORT TO AUTHORIZED HAZARDOUS WASTE TREATMENT FACILITY. CAREFULLY FLUSH RESIDUE TO SANITARY SEWER SYSTEM WITH LARGE VOLUME OF COLD WATER. REPORTABLE QUANTITY = 2,703 LBS.

This product does not contain a reportable quantity (RQ) under CERCLA.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD SUPER KLEEN

MSDS ID: 07657

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: STORE CONTAINER TIGHTLY CLOSED IN COOL, DRY LOCATION.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GOGGLES OR FACE SHIELD
PROTECTIVE GLOVES: RUBBER GLOVES
OTHER PROTECTIVE CLOTHING/EQUIPMENT: LONG-SLEEVED CLOTHING
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: NORMAL AIR DILUTION
LOCAL VENTILATION: NONE

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

BOILING POINT (DEG F): N/A	FREEZING POINT: Not determined
SPECIFIC GRAVITY/BULK DENSITY:	
pH:	pH 1% SOLUTION: Not Determined
VOLATILE BY VOLUME: 1	
VAPOR PRESSURE(mmHg): N/A at	VAPOR DENSITY: N/A

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: CARBON DIOXIDE, CARBON MONOXIDE, CHLORINE
HAZARDOUS DECOMPOSITION PRODUCTS: None known.
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

No data available.
TOXICITY TEST DATA:
No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA: No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.
TRIPLE RINSE CONTAINER WITH COLD WATER, THEN DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD SUPER KLEEN**MSDS ID: 07657**

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: Lb/Gal VOC:

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 1

PERSONAL PROTECTIVE EQUIPMENT: X

NFPA RATING: HEALTH: FIRE: REACTIVITY: SPECIAL:

STATE RIGHT-TO-KNOW INFORMATION:

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.