
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD ASPHALT/TAR REMOVER**MSDS ID: 07861**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Product Discriptor:

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800) 851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
OXFORD ASPHALT/TAR REMOVER		>30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

ACUTE: HARMFUL OR FATAL IF SWALLOWED. IRRITATING TO SKIN AND EYES.
EXCESSIVE INHALATION OF VAPORS CAN CAUSE DIZZINESS, HEADACHE,
FATIGUE AND RESPIRATORY IRRITATION.

CHRONIC: SAME AS ACUTE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: SENSITIVE SKIN AND EYES

IV. FIRST AID MEASURES

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): 135

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: N/K

UEL: N/K

EXTINGUISHING MEDIA: FOAM, DRY CHEMICALS, CO2

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure
breathing apparatus (SCBA) in fire area.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

DIKE AREA TO CONTAIN SPILL; PUMP LIQUID TO SUITABLE CONTAINER. PICK UP RESIDUE
ON ABSORBENT MATERIAL. TRANSPORT TO AUTHORIZED HAZARDOUS CHEMICAL WASTE
TREATMENT FACILITY. EXTINGUISH ALL SOURCES OF IGNITION. PROVIDE SUPPLIED-AIR
RESPIRATORS TO ALL CLEANUP PERSONNEL.

This product does not contain a reportable quantity (RQ) under CERCLA.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD ASPHALT/TAR REMOVER

MSDS ID: 07861

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: STORE IN A COOL, DRY LOCATION. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: SOLVENT-RESISTANT, SUCH AS POLYETHYLENE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: NORMAL AIR DILUTION
LOCAL VENTILATION: YES

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

BOILING POINT (DEG F): 318	FREEZING POINT: Not determined
SPECIFIC GRAVITY/BULK DENSITY:	
pH:	pH 1% SOLUTION: Not Determined
VOLATILE BY VOLUME: 90	
VAPOR PRESSURE(mmHg): 33 at 20 C	VAPOR DENSITY: N/A

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: CO2, CARBON MONOXIDE, HYDROGEN CHLORIDE AND SMALL AMOUNTS OF PHOSGENE
HAZARDOUS DECOMPOSITION PRODUCTS: None known.
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

No data available.
TOXICITY TEST DATA:
No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA: No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.
TRIPLE RINSE CONTAINER WITH COLD WATER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD ASPHALT/TAR REMOVER**MSDS ID: 07861**

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: Lb/Gal VOC:

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 2 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: C

NFPA RATING: HEALTH: FIRE: REACTIVITY: SPECIAL:

STATE RIGHT-TO-KNOW INFORMATION:

N/A

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.