
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD SPECIAL ALUMINUM BRIGHT**MSDS ID: 07909**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Product Descriptor:

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800) 851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
OXFORD SPECIAL ALUMINUM BRIGHT		>30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: CAUSES SEVERE BURNS WHICH MAY NOT BE IMMEDIATELY PAINFUL OR VISIBLE.
HARMFUL IF SWALLOWED.

CHRONIC: SAME AS ACUTE

IV. FIRST AID MEASURES

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA: WATER

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure
breathing apparatus (SCBA) in fire area.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

WEAR FULL PROTECTIVE CLOTHING. VENTILATE AREA. DILUTE SMALL SPILL AND
CAREFULLY NEUTRALIZE WITH SODA ASH. FLUSH RESIDUE TO SANITARY SEWER WITH
WATER. DIKE LARGE SPILL WITH ABSORBENT MATERIAL. PUMP LIQUID TO INTACT
CONTAINER. CAREFULLY NEUTRALIZE RESIDUE WITH SODA ASH. FLUSH RESIDUE TO SEWER
SYSTEM. TRANSPORT ABSORBENT MATERIAL TO HAZARDOUS WASTE.

This product does not contain a reportable quantity (RQ) under CERCLA.

OXFORD SPECIAL ALUMINUM BRIGHT

MSDS ID: 07909

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: STORE TIGHTLY SEALED AWAY FROM ALKALIS AND EXCESSIVE HEAT. DO NOT STORE IN GLASS CONTAINERS. ANYONE WHO KNOWS OR SUSPECTS HE HAS COME IN CONTACT WITH HYDROFLUORIC ACID SHOULD FOLLOW FIRST AID DIRECTIONS AND SEEK MEDICAL ATTENTION IMMEDIATELY.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES OR FACE SHIELD

PROTECTIVE GLOVES: POLYVINYL CHLORIDE (PVC) GLOVES

OTHER PROTECTIVE CLOTHING/EQUIPMENT: RUBBER APRON, RUBBER BOOTS, LONG-SLEEVED CLOTHING

ENGINEERING CONTROLS:

MECHANICAL VENTILATION: GOOD GENERAL VENTILATION

LOCAL VENTILATION: YES

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

BOILING POINT (DEG F): 220

FREEZING POINT: Not determined

SPECIFIC GRAVITY/BULK DENSITY:

pH:

pH 1% SOLUTION: Not Determined

VOLATILE BY VOLUME: 6

VAPOR PRESSURE(mmHg): 25.4 at 20 C

VAPOR DENSITY: 0.63

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE

INCOMPATIBILITY WITH OTHER MATERIALS: CARBON DIOXIDE, CARBON MONOXIDE, HYDROGEN FLUORIDE

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

No data available.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA: No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

TRIPLE RINSE CONTAINER WITH COLD WATER, THEN DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT REUSE CONTAINER.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

OXFORD SPECIAL ALUMINUM BRIGHT**MSDS ID: 07909**

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: Lb/Gal VOC:

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: X

NFPA RATING: HEALTH: FIRE: REACTIVITY: SPECIAL:

STATE RIGHT-TO-KNOW INFORMATION:

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.