

I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 0817

PRODUCT NAME: **RG-40647**

USE: Sanitizing Teat Dip

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: not applicable

CHEMICAL FAMILY: Biguanide

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Isopropanol	1-5	000067-63-0	LD50 5045 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: not required

Eye: safety glasses

Footwear: not required

Respiratory: If mists are generated, use NIOSH approved mask

Other: not applicable

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Do not store above 60°C. Avoid freezing.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): anionic materials

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, dark blue liquid - alcohol odour

S.G. / BULK DENSITY(g/cc): 1.00

pH: 4.6 - 5.8

VAPOUR PRESSURE (mmHg): not applicable

VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not applicable

BOILING POINT: approx. 100°C

FREEZING POINT: approx. 0°C

PERCENT VOLATILE: 90%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): not applicable

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause irritation.

SKIN: No serious or irreversible effects expected.

INGESTION: May cause irritation of digestive tract.

INHALATION: No serious or irreversible effects expected.

LD50 (calculated): > 5000 mg/kg

LC50 (calculated): not available

OTHER TOXIC EFFECTS: Isopropanol TWA 400 ppm	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: not available	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician.
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician.
INHALATION:	Remove patient to fresh air.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: Yes, combustible if heated.	
FLASH POINT, °C: 52°C, (TCC)	AUTO IGNITION TEMPERATURE, °C: N/Av
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: not applicable	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: not applicable	
INCOMPATIBILITY (Material to Avoid) : Anionic materials will inactivate the product.	
HAZARDOUS DECOMPOSITION PRODUCTS: not applicable	
REACTIVITY: not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: RTECS	PREPARED BY: JohnsonDiversey Canada. Inc. Regulatory Department Industrial Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	