

MATERIAL SAFETY DATA SHEET



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 0827

PRODUCT NAME: BRILL SHEEN

USE: Acid Circulation Cleaner

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: E TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: mineral acid CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Sulphuric acid	1-5	007664-93-9	LD50 2140 mg/kg	oral/rat
Phosphoric acid	10-30	007664-38-2	LD50 1530 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Neoprene, Nitrile Eye: safety goggles Footwear: not normally required

Respiratory: If mists are generated, use NIOSH approved **Other:** Rubber apron

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Do not breathe mist, spray or vapours. Avoid eye and skin contact.

VENTILATION REQUIREMENTS: mechanical exhaust

INCOMPATIBILITY (Material to Avoid): Alkaline and chlorinated materials. Organic materials.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN1760

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, red liquid

S.G. / BULK DENSITY(g/cc): 1.13 **pH:** < 1.0

VAPOUR PRESSURE (mmHg): not applicable VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not available BOILING POINT: 100°C

FREEZING POINT: not available PERCENT VOLATILE: 80%

SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): not applicable

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly.

INHALATION: May cause irritation of respiratory tract.

LD50 (calculated): 8100 mg/kg LC50 (calculated): not available

OTHER TOXIC EFFECTS: TLV-TWA 1 mg/m3 as Sulphuric Acid. IARC has classified "occupation! exposure to strong acid mists containing

sulphuric acid" as being carcinogenic to humans. The route of entry is inhalation of these mists resulting in

respiratory (laryngeal) cancers. There is no evidence that the liquid is in any way a carcinogen.

EFFECTS OF CHRONIC

not available

EXPOSURE TO MATERIAL:

VI - FIRST AID MEASURES

EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.

SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.

INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a

physician immediately.

INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.

VII - FIRE AND EXPLOSION DATA

FLAMMABLE: No. Will generate explosive hydrogen gas on contact with metals.

FLASH POINT, °C: not applicable AUTO IGNITION TEMPERATURE, °C: N/Ap

EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.

HAZARDOUS COMBUSTION PRODUCTS: not applicable.

EXPLOSIVE SENSITIVITY TO: not applicable

VIII - REACTIVITY DATA

STABILITY: Stable [x] Unstable []

CONDITIONS TO AVOID: not applicable.

INCOMPATIBILITY (Material to Avoid): Alkaline and chlorinated materials. Aluminium, brass, copper, iron, mild steel. Organic materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

Contact with chlorinated materials will release chlorine gas. Contact with alkali will generate heat. Contact with soft metals forms flammable hydrogen gas. Contact with organic

materials will generate heat.

REACTIVITY: not dangerously reactive

IX - MSDS PREPARATION

SOURCES USED: RTECS, Industrial Chemicals Safety Manual PREPARED BY: JohnsonDiversey Canada, Inc.

Regulatory Department

PREPARATION DATE: April 15, 2003 Food Division

Phone (905) 829-1200

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.