



## **MATERIAL SAFETY DATA SHEET**



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 0828						
PRODUCT NAME: SUPER DICOLOID						
USE: Acid Circulation Cleaner						
SUPPLIER:			EMERGENCY PHONE:			
JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada		1-800-668-7171				
WHMIS CLASSIFICATION:       D1A       E         CHEMICAL FAMILY:       mineral acid		TRADE NAME / SYNONYMS:       not applicable         CHEMICAL NAME:       not applicable				
II - HAZARDOUS INGREDIENTS						
HAZARDOUS INGREDIENT	% w/w	1	CAS #	LD50 / LC50	Route / Species	
Nitric acid Phosphoric acid	5-10 10-30		007697-37-2 007664-38-2	LC50 49 ppm/4H LD50 1530 mg/kg	inh/rat oral/rat	
III - HANDLING AND DISPOSAL PROCEDURES						
PERSONAL PROTECTIVE EQUIPMENT:         Gloves:       Natural Rubber, Neoprene or Nitrile       Eye:       safety goggles       Footwear:       not required         Respiratory:       If mists are generated, use NIOSH approved mask       Other:       Impermeable apron         SPECIAL HANDLING PROCEDURES AND EQUIPMENT:       Do not breathe mist, spray or vapours. Avoid eye and skin contact.         VENTILATION REQUIREMENTS:       mechanical exhaust.         INCOMPATIBILITY (Material to Avoid):       Alkaline and chlorinated materials. Organic materials.         SPILL PROCEDURES:       Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.         WASTE DISPOSAL:       Dispose according to municipal, provincial, and federal regulations.         STORAGE / SHIPPING REQUIREMENT:       Store in a cool dry area in a closed container.						
STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN1760 IV - PHYSICAL PROPERTIES						
APPEARANCE / ODOUR: Clear, red liquid						
S.G. / BULK DENSITY(g/cc): 1.19		<b>pH:</b> <1.0				
VAPOUR PRESSURE (mmHg): not applicable			VAPOUR DENSITY (air=1): not applicable			
ODOUR THRESHOLD: not available			BOILING POINT: 100°C			
FREEZING POINT: not available			PERCENT VOLATILE: 70%			
SOLUBILITY IN WATER: soluble			EVAPORATION RATE (water=1): not applicable			
V - TOXICOLOGICAL PROPERTIES						
EFFECTS OF ACUTE EXPOSURE TO MATERIAL:         EYES:       Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.         SKIN:       Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.         INGESTION:       Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly.         INHALATION:       May cause irritation of respiratory tract.						
LD50 (calculated): not available			LC50 (calculated): not available			

OTHER TOXIC EFFECTS: TLV (Phosphoric acid): TWA 1mg/m3, STEL mg3/m3; TLV (Nitric acid) TWA 2 ppm (~ 5 mg/m3),						
STEL 4 ppm (~ 10 mg/m3)         EFFECTS OF CHRONIC       not available         EXPOSURE TO MATERIAL:						
VI - FIRST AID MEASURES						
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.						
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.						
<b>INGESTION:</b> Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.						
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty. VII - FIRE AND EXPLOSION DATA						
FLAMMABLE: No. Will generate explosive hydrogen gas on contact with metals.						
FLASH POINT, °C: not applicable						
	Dioxide [x] Foam [x] Other [ ]					
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.						
HAZARDOUS COMBUSTION PRODUCTS: Oxides of nitrogen.						
EXPLOSIVE SENSITIVITY TO: not applicable						
VIII - REACTIVITY DATA						
STABILITY: Stable [x] Unstable []						
CONDITIONS TO AVOID: not applicable						
INCOMPATIBILITY (Material to Avoid) : Alkaline and chlorinated	materials. Aluminium, brass, copper, iron, mild steel. Organic materials.					
HAZARDOUS DECOMPOSITION PRODUCTS: Contact with chlorinated materials will release chlorine gas. Contact with alkali will generate heat. Contact with soft metals forms flammable hydrogen gas. Contact with organic materials will generate heat.						
REACTIVITY: not dangerously reactive						
IX - MSDS PR	IX - MSDS PREPARATION					
SOURCES USED: RTECS, Industrial Chemicals Safety Manual.	PREPARED BY: JohnsonDiversev Canada, Inc. Regulatory Department					
PREPARATION DATE: April 15, 2003	Food Division Phone (905) 829-1200					
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.						