

PRINT MIST OIL 32

MSDS ID: 09729

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PRINT MIST OIL 32
PRODUCT DESCRIPTOR: PETROLEUM LUBRICATING OIL WITH INHIBITORS
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
PETROLEUM HYDROCARBON 64742-54-7	<70	TLV 5; PEL 5; ST 10 (OIL MIST)	MG/M3
PETROLEUM HYDROCARBON 64742-65-0	<40		

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: NO
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: DEFATS SKIN; MAY IRRITATE EYES.
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.
INGESTION: GIVE WATER, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION.

V. FIRE FIGHTING MEASURES

FLASH POINT: 375 DEG F FLAME EXTENSION: N/A IN.
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A
UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE KNOWN
EXTINGUISHING MEDIA: CO2, DRY CHEMICALS, OTHERS SUITABLE FOR
CLASS B FIRES.
FIRE FIGHTING INSTRUCTIONS: HANDLE AS PETROLEUM LUBRICANT; CONTAINER
MAY BE COOLED BY WATER.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PRINT MIST OIL 32

MSDS ID: 09729

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: CONTAIN THE SPILL. PREVENT SPILL FROM ENTERING SEWER. RECOVER FREE LIQUID AND/OR COLLECT WITH INERT OIL ABSORBENT. PLACE ABSORBENT INTO METAL CONTAINER FOR DISPOSAL. CLEAN SPILL AREA WITH DETERGENT OR SOLVENTIZED CLEANER.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: STORE CONTAINERS CLOSED IN A CLEAN, DRY AREA. KEEP AWAY FROM HEAT, OPEN FLAME, AND OXIDIZING AGENTS. DO NOT PRESSURIZE CONTAINER TO EMPTY.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD OR GOGGLES
PROTECTIVE GLOVES: RUBBER OR NEOPRENE
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: CLOTHING TO PREVENT PROLONGED SKIN CONTACT.
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): >600 SPECIFIC GRAVITY: 0.8700
VOLATILE BY VOLUME: 0 SOLUBILITY IN WATER: 0
VAPOR PRESSURE (MMHG): <0.1 AT 20 C
APPEARANCE AND ODOR: FLUORESCENT GREEN LIQUID OIL; MILD PETROLEUM ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: STRONG ACIDS AND ALKALIS WILL AFFECT QUALITY. STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION PRODUCTS: EXTREME HEAT (BURNING)-CARBON CARBON MONOXIDE
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER TRIPLE RINSE WITH KEROSENE OR AVAILABLE SOLVENT, BURN LIQUID DISPOSE AS WASTE OIL OR SOLVENT REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL RE-REFINER; LANDFILL APPROVED FOR PETROLEUM PRODUCTS. ALL CHEMICAL

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PRINT MIST OIL 32

MSDS ID: 09729

XIII. DISPOSAL CONSIDERATIONS (Cont.)

COMPONENTS ARE LISTED ON THE TSCA INVENTORY.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC

CAS #64742-54-7

PETROLEUM HYDROCARBONS - CAS #64742-65-0

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.