

P.O.G.

MSDS ID: 09885

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: P.O.G.

Product Code: 09885

Product Function: PAINT, OIL & GREASE REMOVER

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH 45241-2046

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient Name(CAS Number)	%	Exposure Limits	
PETROLEUM DISTILLATE (64742-94-5)	<50	TLV 200; PEL NE	PPM
METHYL ISOBUTYL KETONE (108-10-1)	<10	TLV 50; PEL 100	PPM
DIPROPYLENE GLYCOL MONOMETHYL	<10	TLV 100; PEL 100	PPM
ETHER (34590-94-8)			
CYCLOHEXANOL (108-93-0)	<15	TLV 50; PEL 50	PPM

3. HAZARDS IDENTIFICATION

Possible Routes of Entry:

Inhalation: YES

Skin: YES

Ingestion: YES

4. FIRST AID MEASURES

Eyes: FLUSH THOROUGHLY WITH FRESH WATER, FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

Skin: FLUSH WITH FRESH WATER FOR 15 MINUTES, WASH WITH SOAP AND WATER REMOVE CONTAMINATED CLOTHES AND SHOES

Ingestion: GIVE WATER, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Inhalation: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF BREATHING IS DIFFICULT.

5. FIRE FIGHTING MEASURES

Flash Point (degrees F): 120

Unusual Fire or Explosion Hazards: COMBUSTIBLE - RESIDUE MAY BURN IF ALL LIQUID IS EVAPORATED BY HEAT AND FIRE.

Extinguishing Media: FOAM, DRY CHEMICAL

Fire Fighting Instructions: WEAR FULL PROTECTIVE GEAR TO PREVENT SKIN CONTACT AND SCBA.

6. ACCIDENTAL RELEASE MEASURES

If Material is Released or Spilled:

SOAK UP SPILLED LIQUIDS WITH SUITABLE ABSORBENT, PACKAGE AND DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT DISCHARGE TO SANITARY SEWER SYSTEM AS PRODUCT EMULSIFIES IN WATER. CERCLA PRODUCT RQ: NO

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 1/06/05

P.O.G.

MSDS ID: 09885

6. ACCIDENTAL RELEASE MEASURES (Cont.)

REPORTABLE QUANTITY.

7. HANDLING AND STORAGE

COMBUSTIBLE LIQUID. KEEP FROM FREEZING. KEEP AWAY FROM ACIDS AND OXIDIZERS. DO NOT STORE NEAR HEAT OR OPEN FLAME. DO NOT PRESSURE CONTAINER TO EMPTY.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye/Face Protection: FACE SHIELD, SIDE SHIELD SAFETY GLASSES
Protective Gloves: CHEMICAL RESISTANT, RUBBER, OR PVC
Respiratory Protection: USUALLY NOT REQUIRED. MONITOR AREAS FOR CONTAMINATION IF SYMPTOMS OF OVEREXPOSURE ARE EVIDENT.
Other Protective Clothing/Equipment: CHEMICALLY IMPERVIOUS CLOTHING AND FOOTWEAR; SAFETY SHOWER/EYE WASH IN USE AREA.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: YELLOW LIQUID; SOLVENT ODOR.
Boiling Point (F): 208 Freezing Point: NOT DETERMINED
Specific Gravity: 0.9200
Volatile (by Vol.): >80 Solubility in Water: EMUL
pH:

10. STABILITY AND REACTIVITY

Chemical Stability: STABLE
Incompatibility With Other Materials: OXIDIZING AGENTS, CHLORINATED CLEANERS, HEAT SOURCES
Hazardous Decomposition Products: CO₂, CO WITH IMCOMPLETE COMBUSTION
Hazardous Polymerization: None

11. TOXICOLOGICAL INFORMATION

Signs and Symptoms of Overexposure:
Acute: IRRITATES OR DEFATS SKIN. IRRITATES EYES. OVEREXPOSURE TO VAPOR OR MIST MAY CAUSE HEADACHE DIZZINESS OR NAUSEA. INGESTION CAUSES IRRITATION OF GASTRIC TISSUE.
Chronic: NO KNOWN CHRONIC HAZARDS.
Medical Conditions Generally Aggravated by Exposure: SENSITIVE SKIN, RESPIRATORY CONDITIONS

12. ECOLOGICAL INFORMATION

No data available

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 1/06/05

P.O.G.

MSDS ID: 09885

13. DISPOSAL CONSIDERATIONS

USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER, TRIPLE RINSE WITH WATER AND ADD TO OPERATION. REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL. CONSULT LOCAL OR STATE REGULATIONS REGARDING HAZARDOUS WASTE DISPOSAL. DO NOT DISCHARGE TO SANITARY SEWER, OR PONDS, LAKES, STREAMS. TREAT AS PROCESS WASTE OIL.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

THIS PRODUCT CONTAINS THE FOLLOWING SARA TITLE III SECTION 313 REPORTABLE CHEMICALS: METHYL ISOBUTYL KETONE (108-10-1) AT 7% AND DIPROPYLENE GLYCOL MONOMETHYL ETHER (34590-94-8) AT 5%.

CARCINOGENICITY:

Not listed as carcinogenic by IARC, NTP, OSHA, ACGIH.

HMIS Ratings: Health: 2 Fire: 2 Reactivity: 0
Personal Protective Equipment: B

State Right-to-Know Information:

METHYL ISOBUTYL KETONE - CAS #108-10-1

CYCLOHEXANOL - CAS #108-93-0

POTASSIUM OLEATE - CAS #143-18-0

WATER - CAS #7732-18-5

DIPROPYLENE GLYCOL MONOMETHYL ETHER - CAS #34590-94-8

PETROLEUM DISTILLATE - CAS #64742-94-5

16. OTHER INFORMATION

DISCLAIMER: The information contained in this safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the applicability of this information for their particular conditions of storage, handling, and use.