NEXUS DC-3600

Page Revised Replaces 2/03/04 Printed

1 of 4 2/02/04 8/12/03

MSDS ID: 11019

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: NEXUS DC-3600

Product Descriptor: ROLL TREATMENT AGENT

MANUFACTURER: JOHNSONDIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800)851-7145

3630 E. KEMPER ROAD CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

CAS Number Component Name Exposure Limits Units

68439-46-3 5 - 15% LINEAR ALCOHOL ETHOXYLATE None est.

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING - Contains chemicals that cause irritation to eyes and skin. May be harmful if swallowed. Wear eye protection, clothing and rubber gloves to prevent prolonged skin contact. Wash after handling.

POSSIBLE ROUTES OF ENTRY: Skin contact/absorption

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Severe irritation with redness, pain and swelling. SKIN: ACUTE:

> Irritation or dryness develops with long contact. INGESTION: Ιf swallowed, pain, nausea and vomiting may result. INHALATION:

Causes irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive

skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and GI tract.

IV. FIRST AID MEASURES

Immediately flush eyes with plenty of water for 15 minutes. Get EYES:

medical attention.

Flush skin with plenty of water and wash with mild soap. If SKIN:

irritation develops, get medical attention.

If swallowed, rinse mouth with water. Dilute by drinking several INGESTION:

> glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never

give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air and seek medical attention.

NEXUS DC-3600

Page 2 of 4 Revised 2/02/04

Replaces 8/12/03 2/03/04 Printed

MSDS ID: 11019

# V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): None FLAME EXTENSION: N/A FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/E UEL: N/E

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure

breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

# VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

# VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area. Keep from freezing. Keep away from alkalis and chlorinated products. Do not pressurize container to empty.

# VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. PROTECTIVE GLOVES: Acid resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

# IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear, odorless liquid, mild odor.

BOILING POINT (DEG F): 212 F FREEZING POINT: <32 F

SPECIFIC GRAVITY/BULK DENSITY: 1.01

pH: pH 1% SOLUTION: NA

VOLATILE BY VOLUME: 88

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHq): 17.5 at 20 C VAPOR DENSITY: 17.3

3 of 4 Page Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 11019

NEXUS DC-3600

# X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents; Alkalis HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of

HAZARDOUS POLYMERIZATION: None known.

#### XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: Toxicological testing has not been performed on the

product. Listed below is the available toxicology test

data for components of the product.

TOXICITY TEST DATA:

Alcohol Ethoxylates (CAS# 68439-46-3):

Acute Oral LD50 (rat) 1.4 gm/kg Acute Dermal LD50 (rabbit) 5 gm/kg Eye Irritation (rabbit) Severe Skin Irritation (rabbit) Draize 1.2 (4 hrs.)

# XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

# XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Adjust pH of diluted product and discharge to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container according to product labeling or Federal, State or local regulations.

### XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

# XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

CHRONIC:NO FIRE:NO ACUTE: YES REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

NEXUS DC-3600

Page 4 of 4 Revised 2/02/04 Replaces 8/12/03

2/03/04 Printed

MSDS ID: 11019

# XV. REGULATORY INFORMATION (Cont.)

LISTED CARCINOGEN: None

IARC: No OSHA: NO NTP: NO

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY: 0 SPECIAL: ACID

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

POLYDIMETHYL AMMONIUM CHLORIDE - CAS #26062-79-3

LINEAR ALCOHOL ETHOXYLATE - CAS #68439-46-3

TRIDECETH 7 - CARBOXYLIC ACID - PROPRIETARY

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

#### XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.