



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 11067

PRODUCT NAME: VARI-CLEAN 305S

USE: Solventized press fabric cleaning concentrate

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: B3 E

CHEMICAL FAMILY: caustic alkali

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Sodium hydroxide	10-30	001310-73-2	LDlo 500 mg/kg	oral/rat
Sodium dodecylbenzene sulphonate	1-5	025155-30-0	LD50 1260 mg/kg	oral/rat
D-limonene	10-30	005989-27-5	LD50 4400 mg/kg	oral/rat
Alcohol ethoxylate	5-10	068439-46-3	LD50 1400 mg/kg	oral/rat
Dipropylene glycol methyl ether	1-5	034590-94-8	LD50 5200 mg/kg	oral/rat
Propylene glycol	7-13	000057-55-6	LD50 20000 g/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Neoprene or nitrile

Eye: Safety goggles

Footwear: Rubber boots

Respiratory: If mists are generated, use NIOSH approved mask

Other: Rubber apron, face shield

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. Do not breathe mist or spray.

VENTILATION REQUIREMENTS: General ventilation

INCOMPATIBILITY (Material to Avoid): Acidic material, aluminum, zinc

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Neutralize with dilute acid. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Avoid freezing.

UN2920

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear red-brown liquid

S.G. / BULK DENSITY(g/cc): 1.16

pH: (1% solution): 12.4

VAPOUR PRESSURE (mmHg): not available

VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not available

BOILING POINT: >100°C

FREEZING POINT: not available

PERCENT VOLATILE: approx. 28%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): Approx. 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

INGESTION: May cause irritation of the digestive tract. May cause nausea, vomiting and diarrhea.	
INHALATION: Breathing spray or mist may cause respiratory irritation. May cause headache, drowsiness and dizziness.	
LD50 (calculated): 1866 mg/kg	LC50 (calculated): Not applicable
OTHER TOXIC EFFECTS: Sodium Hydroxide TLV-CL 2 mg/m3; Propylene Glycol 50 ppm AIHA WEEL; TLV: TWA (Dipropylene glycol methyl ether): 606 mg/m3 (100 ppm)	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: None known.	
VI - FIRST AID MEASURES	
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.	
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.	
INGESTION: Drink large volumes of water. Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.	
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.	
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: Yes, combustible if heated.	
FLASH POINT, °C: 47°C (Pensky-Martens)	AUTO IGNITION TEMPERATURE, °C: N/Ap.
EXTINGUISHING MEDIA: Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, sulphur.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: High temperature	
INCOMPATIBILITY (Material to Avoid) : Acidic materials, aluminum and other soft metals.	
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with acids. Contact with aluminum or soft metals may release flammable hydrogen gas.	
REACTIVITY: Not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: MSDS, RTECS.	PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Industrial Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	