VARI-CLEAN 480S

Page 1 of 4 Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 11072

# I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: VARI-CLEAN 480S

Product Descriptor: SOLVENTIZED PRESS FABRIC CLEANING CONCENTRATE

MANUFACTURER: JOHNSONDIVERSEY, INC. EMERGENCY PHONE NUMBER: (800)851-7145

3630 E. KEMPER ROAD CINCINNATI, OH. 45241

	II. HAZARDOUS COMPONENTS		
Component Name	CAS Number %	Exposure Limits	Units
PETROLEUM DISTILLATES POTASSIUM HYDROXIDE	8008-20-6 >30% 1310-58-3 1 - 5%	TWA 400 TWA - C 2	PPM MG/M3

## III. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW:

CORROSIVE MATERIAL - Causes severe burns to skin and eyes. Harmful if swallowed. Do not contact eyes, skin or clothing. Avoid breathing any dust, spray mist or vapors in spill area. Wash thoroughly after handling product. Wear eye protection, clothing and footwear to prevent skin contact. POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

## SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe burns or irritation with pain, redness, swelling, and blurred or impaired vision. SKIN: Burns, blisters or rash with pain and swelling. INGESTION: Burns or irritation to mouth, throat with pain, nausea and vomiting. INHALATION: Overexposure to vapors may cause dizziness, headache, fatigue and respiratory irritation.

CHRONIC: (Petroleum Distillates) Asthma or reactive airway disease.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

## IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15

minutes. Hold eyelids apart to completely flush all chemicals from

entire eye surface. Get immediate medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with mild soap and

water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured

skin.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several

glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never

give fluids by mouth to an unconscious person.

VARI-CLEAN 480S

Page 2 of 4 Revised 2/02/04 Replaces 8/12/03 2/03/04

Printed

MSDS ID: 11072

# IV. FIRST AID MEASURES (Cont.)

INHALATION: If inhaled, move to fresh air. If patient is not breathing, give artificial respiration. If breathing is difficult, give oxygen

under the direction of trained personnel or a physician.

immediate medical attention.

# V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): 142F FLAME EXTENSION: N/A FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/E UEL: N/E

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: COMBUSTIBLE. Avoid sparks or open flames.

Toxic fumes or vapor may form during fire. Liquid produces hydrogen on contact with soft, active metals.

EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

## VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

# VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: COMBUSTIBLE PRODUCT. Do not store near heat, sparks or open flames. Keep container closed when not in use. Product may accumulate a static charge. Use proper grounding during storage or emptying container. Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

# VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. Face shields.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots and chemical resistant apron if contact or splash hazard exists. Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

VARI-CLEAN 480S

Page 3 of 4 Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 11072

# IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

BOILING POINT (DEG F): 212F FREEZING POINT: N/D

SPECIFIC GRAVITY/BULK DENSITY: 0.91

ph: 13 ph 1% SOLUTION: N/D

VOLATILE BY VOLUME: 67.6% SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 0.48 at 20 VAPOR DENSITY: 4.5

# X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of

carbon; oxides of sulfur

HAZARDOUS POLYMERIZATION: None known.

#### XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: Toxicological testing has not been performed on the

product. Listed below is the available toxicology test

data for components of the product.

TOXICITY TEST DATA:

Potassium Hydroxide:

Acute Oral LD50 (rat) - 365 mg/kg (RTECS)

Acute Skin LD50 (rabbit) - 1260 mg/kg (MSI

Linear Alcohol Ethoxylate (CAS# 68131-39-5):

Acute Oral LD50 rat 1800 mg/kg

#### XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

## XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Product is considered to be D002- Corrosive, if declared

Hazardous Waste.

Spent or excess product is hazardous waste. Do not discharge to sewer or environment. Arrange disposal through a licensed disposal company or treat by special Waste Disposal Sheet. Recycle or dispose of containers by product labeling or governmental regulations.

## XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

VARI-CLEAN 480S

Replaces 8/12/03 Printed

Page

4 of 4 Revised 2/02/04 2/03/04

MSDS ID: 11072

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: 43.8% Lb/Gal VOC: 3.32

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

CHRONIC:NO FIRE:YES REACTIVITY:NO ACUTE: YES

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

IARC: No NTP: No OSHA: No

HMIS RATINGS: HEALTH: 3 FIRE: 2 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 2 REACTIVITY: 0 SPECIAL: Alkali

STATE RIGHT-TO-KNOW INFORMATION:

KEROSENE - CAS #8008-20-6

WATER - CAS #7732-18-5

POTASSIUM HYDROXIDE - CAS #1310-58-3

ALKYL POLYETHOXY GLYCOL - CAS #68131-39-5

POTASSIUM TALLATE - CAS #61790-44-1

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

# XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.