

EVEREST THREE

MSDS ID: 11123

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: EVEREST THREE

Product Descriptor: DEFOAMED ADDITIVE FOR SINGLE STAGE HEAT TREATED SURFACES

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
ETHYLENE DIAMINE TETRAACETIC ACID	60-00-4	5 - 15%	None established	
POTASSIUM HYDROXIDE	1310-58-3	1 - 5%	TWA - C 2	MG/M3
POTASSIUM SILICATE	1312-76-1	1 - 5%	None est.	
TETRASODIUM ETHYLENE DIAMINE TETRAACETATE	64-02-8	15 - 30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE - Contains strong alkali. Causes severe burn to skin and eyes. May be fatal if swallowed. Do not contact eyes, skin or clothing. Wear goggles, face shield, rubber gloves, and protective clothing and boots when handling product. Avoid breathing dust or spray mist. Contain spill or runoff, which may cause environmental damage. Contact with aluminum or soft metals may release flammable hydrogen fumes.

POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe burns, tissue damage, or irritation with pain, swelling, blurred or impaired vision, blindness. SKIN: Severe burns, tissue destruction, blisters or rash with swelling and pain. INGESTION: Burns or irritation to mouth, throat with pain, nausea and vomiting. INHALATION: Spray or mist causes severe irritation with pain, choking, and breathing difficulty.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin, respiratory tract, and gastrointestinal tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids apart to completely flush all chemicals from entire eye surface. Get immediate medical attention.

SKIN: Promptly flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and footwear. Launder contaminated clothing and discard or thoroughly clean shoes before

EVEREST THREE

MSDS ID: 11123

IV. FIRST AID MEASURES (Cont.)

reuse. Get medical attention for painful, red or injured skin areas.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: If inhaled, move to fresh air. If patient is not breathing, give artificial respiration. If breathing is difficult, give oxygen under the direction of trained personnel or a physician. Get immediate medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: NONE UEL: NONE

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire. Liquid produces hydrogen on contact with soft, active metals.

EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: STRONG CAUSTIC PRODUCT. Wear protective gear when using or handling. Product freezes below 50 deg. F. Thaw by warming to 70 deg. F and mix for use. Add product slowly with mixing to water or liquids to avoid heat, steam and spattering. Do not allow product to collect on bottom of tank to prevent violent reaction. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. Face shields.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots and chemical resistant apron

EVEREST THREE

MSDS ID: 11123

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION (Cont.)

if contact or splash hazard exists. Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

BOILING POINT (DEG F): 212

FREEZING POINT: <50 F

SPECIFIC GRAVITY/BULK DENSITY: 1.32

pH: 14

pH 1% SOLUTION: 12.1

VOLATILE BY VOLUME: 46

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 15-17 at 20 C

VAPOR DENSITY: >1

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Soft metals

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of carbon; oxides of nitrogen; oxides of sulfur

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

TOXICITY TEST DATA:

Potassium Hydroxide:

Acute Oral LD50 (rat) - 365 mg/kg (RTECS)

Acute Skin LD50 (rabbit) - 1260 mg/kg (MSI)

Ethylene Diamine Tetraacetic Acid:

Acute Oral LD50 (rat) - 4100 mg/kg

XII. ECOLOGICAL INFORMATION

Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

ECOTOXICITY TEST DATA:

Potassium Hydroxide:

Acute LC50 (96 hr.) (Pimephles promelas) - 179 mg/l

Acute LC50 (96 hr.) (Daphnia magna) - 60 mg/l

ETHYLENE DIAMINE TETRAACETIC ACID:

Acute LC50 (Lepomis macrochirus)- 550 mg/l

Acute LC50 (Daphnia magna) - 595 mg/l

ENVIRONMENTAL FATE: No data available.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 12/06/04
Replaces 2/02/04
Printed 12/07/04

EVEREST THREE

MSDS ID: 11123

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: PRODUCT IS CONSIDERED TO BE D002-CORROSIVE, IF DECLARED
HAZARDOUS WASTE.

Spent or excess product is hazardous waste. Do not discharge to sewer or environment. Arrange disposal through a licensed disposal company or treat by special Waste Disposal Sheet. Recycle or dispose of containers by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: NONE

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 0 REACTIVITY: 0 SPECIAL: ALKALI

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS# 7732-18-5

POTASSIUM SILICATE - 1312-76-1

ETHYLENE DIAMINE TETRAACETIC ACID - CAS# 60-00-4

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE - CAS# 64-02-8

POTASSIUM HYDROXIDE - CAS# 1310-58-3

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.