ENDURO LT

1 of 4 Page Revised 2/02/04 Replaces 8/12/03

Printed 2/03/04

MSDS ID: 11129

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: ENDURO LT

Product Descriptor: CHLORINATED ALKALINE FOAM CLEANER

MANUFACTURER: JOHNSONDIVERSEY, INC. EMERGENCY PHONE NUMBER: (800)851-7145

3630 E. KEMPER ROAD CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS				
Component Name	CAS Number	%	Exposure Limits	Units
POTASSIUM HYDROXIDE SODIUM HYDROXIDE SODIUM HYPOCHLORITE	1310-58-3 1 1310-73-2 5 7681-52-9 1	5 - 15%	TWA - C 2 TLV-C 2 None established	MG/M3 MG/M3

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE - Contains alkalis and chlorinated chemicals. Causes severe burn to skin and eyes. May be fatal if swallowed. Do not contact eyes, skin or clothing. Wear goggles, face shield, rubber gloves, and protective clothing and boots when handling products. Avoid breathing dust or spray mist. Use respiratory protection for any breathing difficulty. TOXIC CHLORINE VAPORS may be released by fire or mixing with acids or ammonia. Contain spill and runoff, which may cause environmental damage.

POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe burns or irritation with pain, redness, swelling, and blurred or impaired vision. SKIN: Burns, blisters or rash with pain and swelling. INGESTION: Burns or irritation to mouth, throat with pain, nausea and vomiting. INHALATION: Spray or mist causes severe irritation with pain, choking, and breathing difficulty.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin, respiratory tract, and gastrointestinal tract.

IV. FIRST AID MEASURES

Immediately flush eyes with plenty of water for at least 15 EYES:

minutes. Hold eyelids apart to completely flush all chemicals from

entire eye surface. Get immediate medical attention.

Flush thoroughly with plenty of water. Wash with mild soap and SKIN:

water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured

skin.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several

glasses of water. DO NOT induce vomiting. If patient vomits,

ENDURO LT

Page 2 of 4 Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 11129

IV. FIRST AID MEASURES (Cont.)

rerinse mouth. Get immediate medical attention. NOTE: Never

give fluids by mouth to an unconscious person.

INHALATION: If inhaled, move to fresh air. If patient is not breathing, give

artificial respiration. If breathing is difficult, give oxygen under the direction of trained personnel or a physician. Get

immediate medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): None FLAME EXTENSION: N/A FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/E UEL: N/E

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Burning or decomposition may form hydrogen chloride or other toxic gasses. Liquid produces hydrogen on contact with soft, active metals.

EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

The Reportable Quantity (RQ) of Sodium Hypochlorite CAS #7681-52-9 is 352 gallons or 3,540 lbs. The Reportable Quantity (RQ) of Sodium Hydroxide CAS #1310-73-2 is 715 gallons or 7,140 lbs.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: CHLORINATED PRODUCT. Do not mix or store with acids or ammonia containing chemicals. Toxic chlorinated gasses may be released. Keep container closed when not in use. Wear protective gear when handling or using product. Protect from high temperatures.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. Face shields.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Not normally required. If mist is generated, use NIOSH/MSHA aproved respirator with a prefilter for mist.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots and chemical resistant apron if contact or splash hazard exists. Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne

3 of 4 Page Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 11129

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION (Cont.)

levels.

ENDURO LT

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear yellow liquid.

BOILING POINT (DEG F): None FREEZING POINT: <50F

SPECIFIC GRAVITY/BULK DENSITY: 1.2

pH: 13.2 ph 1% SOLUTION: 12.13%

VOLATILE BY VOLUME: 76.5%

SOLUBILITY IN WATER: Soluble

at 20C VAPOR PRESSURE(mmHq): 17.5 VAPOR DENSITY: 17.3

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; hydrogen chloride, chlorine and chlorinated compounds; oxides of sulfur; oxides of

nitrogen; oxides of carbon

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Toxicological testing has not been performed on the product. Listed below is the available toxicology

test data for components of the product.

TOXICITY TEST DATA:

Sodium Hydroxide:

Acute Oral LD50 (rat) 500 mg/kg (RTECS)

Acute Skin LD50 (rabbit) 1350 mg/kg (MSI)

Potassium Hydroxide:

Acute Oral LD50 (rat) - 365 mg/kg (RTECS)

Acute Skin LD50 (rabbit) - 1260 mg/kg (MSI)

Sodium Hypochlorite:

Acute Oral LD50 (rat) - 2840 mg/kg (PTI)

XII. ECOLOGICAL INFORMATION

Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

ECOTOXICITY TEST DATA:

Potassium Hydroxide:

Acute LC50 (96 hr.) (Pimephles promelas) - 179 mg/l

Acute LC50 (96 hr.) (Daphnia magna) - 60 mg/l

ENVIRONMENTAL FATE: No data available.

4 of 4 Page Revised 2/02/04 Replaces 8/12/03

2/03/04

Printed

MSDS ID: 11129

ENDURO LT

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Product is considered to be D002 - Corrosive, if declared

hazardous waste.

Spent or excess product is hazardous waste. Do not discharge to sewer or environment. Arrange disposal through a licensed disposal company or treat by special Waste Disposal Sheet. Recycle or dispose of containers by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

None

SARA Section 311/312:

CHRONIC:NO FIRE:NO ACUTE: YES REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: None

NTP: No OSHA: No IARC: No

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 0 REACTIVITY: 0 SPECIAL: Alkali

STATE RIGHT-TO-KNOW INFORMATION:

- CAS #7732-18-5

POTASSIUM HYDROXIDE - CAS #1310-58-3

SODIUM HYDROXIDE -CAS #1310-73-2

SODIUM HYPOCHLORITE - CAS #7681-52-9

SODIUM XYLENE SULFONATE - CAS #1300-72-7

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.