

UHS FLOOR CLEANER

National Fire Protection Association (NFPA)	Fire Hazard		Hazardous Material Information System (HMIS)	Health	3
	Health	3		Reactivity	0
	Fire Hazard			0	
	Reactivity			0	
Specific Hazard					
Protective Clothing				Emergency Overview	Clear Blue. Green. Liquid. See Section 9. DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED.

Section 1. Chemical Product and Company Identification

Product Name	UHS FLOOR CLEANER	Code	4683
Product Use	Industrial/Institutional: Floor care.	PMS#	433453
MSDS#	114680003	Validation Date	5/4/2004
U.S. Headquarters JohnsonDiversey, Inc. 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.johnsondiversey.com	Canadian Headquarters JohnsonDiversey - Canada, Inc. 2401 Bristol Circle Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131	Print Date	5/4/2004
		Supersedes In Case of Emergency	No Previous Validation (800) 851-7145

Section 2. Composition and Information on Ingredients

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Ammonium Hydroxide	1336-21-6	1-5	Not available.	ORAL (LD50): Acute: 350 mg/kg [Rat].
Monoethanolamine	141-43-5	1-5	OSHA (United States). TWA: 8 mg/m ³ STEL: 15 mg/m ³ ACGIH (United States). TWA: 7.5 mg/m ³ STEL: 15 mg/m ³ ACGIH TLV (United States, 2003). Notes: STEL: 15 mg/m ³ 15 minute(s). STEL: 6 ppm 15 minute(s). TWA: 7.5 mg/m ³ 8 hour(s). TWA: 3 ppm 8 hour(s). OSHA PEL (United States, 1993). Notes: TWA: 6 mg/m ³ 8 hour(s). TWA: 3 ppm 8 hour(s)	ORAL (LD50): Acute: 1720 mg/kg [Rat]. 620 mg/kg [Guinea pig]. 700 mg/kg [Mouse]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit].
2-Butoxyethanol	111-76-2	1-5	OSHA (United States). TWA: 120 mg/m ³ ACGIH (United States). TWA: 97 mg/m ³ ACGIH TLV (United States, 2002 Adoption). TWA: 20 ppm 8 hour(s). OSHA PEL (United States,	ORAL (LD50): Acute: 470 mg/kg [Rat]. 300 mg/kg [Rabbit]. 1200 mg/kg [Guinea pig]. DERMAL (LD50): Acute: 220 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hour(s) [Rat].

Water	7732-18-5	60-100	1993). Skin Notes: TWA: 240 mg/m ³ 8 hour(s). TWA: 50 ppm 8 hour(s) Not available.	Not available.
-------	-----------	--------	---	----------------

Section 3. Hazards Identification

Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health Effects	
<i>Eyes</i>	Corrosive. May cause permanent damage including blindness.
<i>Skin</i>	Corrosive. May cause permanent damage.
<i>Inhalation</i>	May cause irritation and corrosive effects to nose, throat and respiratory tract.
<i>Ingestion</i>	Corrosive. May cause burns to mouth, throat, and stomach.
Medical Conditions Aggravated by Overexposure:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.
See Toxicological Information (section 11)	

Section 4. First Aid Measures

Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product	None known.
Flash Points	None.
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
<i>Eyes</i>	Chemical splash goggles.
<i>Hands</i>	Chemical resistant gloves. Includes: Rubber gloves. Neoprene gloves. Butyl gloves.
<i>Respiratory</i>	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
<i>Feet</i>	Protective footwear.
<i>Body</i>	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Ammoniacal.
Color	Clear Blue. Green.
pH	11.2 to 12 [Basic.]
Specific Gravity	1
Melting/Freezing Point	<0°C (32°F)
Solubility in water	Complete.

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Conditions of Instability	None known.
Incompatibility with Various Substances	Reactive with acids.
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion. Toxic decomposition products include: Oxides of nitrogen.
Hazardous Polymerization	Will not occur.

Section 11. Toxicological Information

Acute toxicity	Corrosive.
Effects of Chronic Exposure	None known.
Other Toxic Effects	None known.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information	Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.
--------------------------	--

Section 14. Transport Information
DOT Classification

DOT Proper Shipping Name Please refer to the Bill of Lading/receiving documents for up to date shipping information.

TDG Classification

TDG Proper Shipping Name Please refer to the Bill of Lading/receiving documents for up to date shipping information.
TDG Class

Section 15. Regulatory Information
Reporting in this section is based on ingredients disclosed in Section 2
US Regulations

Federal SARA 302/304/311/312 hazardous chemicals: Ammonium Hydroxide, Monoethanolamine, 2-Butoxyethanol
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Ammonium Hydroxide, Monoethanolamine, 2-Butoxyethanol
 SARA 313 toxic chemical notification and release reporting: Ammonium Hydroxide, 2-Butoxyethanol
 Clean Water Act (CWA) 311: Ammonium Hydroxide
 CERCLA: Hazardous substances.: Ammonium Hydroxide, 2-Butoxyethanol

State New Jersey spill list: Ammonium Hydroxide, 2-Butoxyethanol
 New Jersey: Ammonium Hydroxide, Monoethanolamine, 2-Butoxyethanol
 New Jersey toxic catastrophe prevention act: Ammonium Hydroxide
 Massachusetts spill list: Ammonium Hydroxide, Monoethanolamine, 2-Butoxyethanol
 Massachusetts RTK: Ammonium Hydroxide, Monoethanolamine, 2-Butoxyethanol
 Pennsylvania RTK: Ammonium Hydroxide, Monoethanolamine, 2-Butoxyethanol

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information Not applicable.

Canadian Regulations

Canadian NPRI Canadian NPRI: 2-Butoxyethanol.

WHMIS Classification CLASS E: Corrosive liquid.

WHMIS Icon



Registered Product Information Not applicable.

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information

Other Special Considerations Not available.

Version 2.01

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.