

END BAC II DISINFECTANT SPRAY

National Fire Protection Association (NFPA)	Fire Hazard Health Reactivity Specific Hazard		Hazardous Material Information System (HMIS)	Health	1
				Fire Hazard	4
				Reactivity	0
Protective Clothing	None required.		Emergency Overview	Colorless. Aerosol. See Section 9. CAUTION: CONTENTS UNDER PRESSURE. May be mildly irritating to eyes. May be mildly irritating to skin.	

Section 1. Chemical Product and Company Identification

Product Name END BAC II DISINFECTANT SPRAY		Code	14742
Product Use Industrial/Institutional: Disinfectant.		PMS#	433113
MSDS# 114740006		Validation Date	4/14/2004
U.S. Headquarters JohnsonDiversey, Inc. 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.johnsondiversey.com	Canadian Headquarters JohnsonDiversey - Canada, Inc. 2401 Bristol Circle Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131	Print Date	4/14/2004
		Supersedes	No Previous Validation
		In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
n-Alkyl Dimethyl Ethylbenzyl Ammonium Chlorides	68956-79-6	.072	Not available.	Not available.
n-alkyldimethylethylbenzyl ammonium chlorides	68391-01-5	.072	Not available.	Not available.
Propane	74-98-6	1-5	OSHA (United States). TWA: 1800 mg/m ³ ACGIH (United States). TWA: 4508 mg/m ³ ACGIH TLV (United States, 2003). Notes: 1998 Adoption. TWA: 2500 ppm 8 hour(s). OSHA PEL (United States, 1993). Notes: TWA: 1800 mg/m ³ 8 hour(s). TWA: 1000 ppm 8 hour(s)	Not available.
Isobutane	75-28-5	10-30		VAPOR (LC50): Acute: 0.0057 ppm 0.25 hour(s) [Rat].
Ethyl Alcohol	64-17-5	30-60	OSHA (United States). TWA: 1900 mg/m ³ ACGIH (United States). TWA: 1880 mg/m ³ ACGIH TLV (United States, 2003). Notes: 1996 Adoption Refers to Appendix A --	ORAL (LD50): Acute: 7060 mg/kg [Rat]. 6300 mg/kg [Rabbit]. 3450 mg/kg [Mouse]. VAPOR (LC50): Acute: 20000 ppm 10 hour(s) [Rat].

Continued on Next Page

			Carcinogens. TWA: 1880 mg/m ³ 8 hour(s). TWA: 1000 ppm 8 hour(s)
--	--	--	---

Section 3. Hazards Identification

Routes of Entry Inhalation. Skin contact. Eye contact.

Potential Acute Health Effects

Eyes May be mildly irritating to eyes.

Skin May be mildly irritating to skin.

Inhalation May be irritating to nose, throat, and respiratory tract.

Ingestion None known.

Medical Conditions Aggravated by Overexposure: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.

See Toxicological Information (section 11)

Section 4. First Aid Measures

Eye Contact Flush immediately with plenty of water. Get medical attention if irritation occurs.

Skin Contact Flush immediately with plenty of water. Get medical attention if irritation occurs.

Inhalation If breathing is difficult: Remove to fresh air. Get medical attention.

Ingestion Have conscious person drink several glasses of water or milk. Immediately get medical attention.

Section 5. Fire Fighting Measures

Flammability of the Product None known.

Flash Points CLOSED CUP: <-7°C (19.4°F).

Products of Combustion None known.

Fire Fighting Media and Instructions Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide. Fight fire from protected location or maximum possible distance. In case of fire and/or explosion do not breathe fumes..

Protective Clothing (Fire) Put on appropriate personal protective equipment (see Section 8).

Special Remarks on Fire and Explosion Hazards Aerosol product - Containers may rocket or explode in heat of fire.

Section 6. Accidental Release Measures

Personal Precautions Put on appropriate personal protective equipment (see Section 8).

Environmental Precautions and Clean-up Methods Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods.

Section 7. Handling and Storage

Handling Avoid contact with skin and eyes. Avoid breathing vapors or spray mists. Use only in well-ventilated areas. Do not puncture or incinerate. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. Pressurized container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls No special ventilation requirements. General room ventilation is adequate.

Personal Protection

Eyes No special requirements under normal use conditions.

Hands No special requirements under normal use conditions.

Respiratory No special requirements under normal use conditions.

Feet No special requirements under normal use conditions.

Body No special protective clothing is required.

Section 9. Physical and Chemical Properties

Physical State and Appearance Liquid. (Aerosol.)

Odor Mild.

Color Colorless.

pH 9.35 [Basic.]

Specific Gravity 0.9

Vapor Pressure 60 mm of Hg

Solubility in water Complete.

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Conditions of Instability Excessive heat.

Incompatibility with Various Substances None known.

Hazardous Decomposition Products When exposed to fire: Produces normal products of combustion.

Hazardous Polymerization Will not occur.

Section 11. Toxicological Information

Acute toxicity Not available.

Effects of Chronic Exposure None known.

Other Toxic Effects Not available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information If possible, recycle empty aerosol cans to the nearest steel recycling center. Use up package or give to someone who can. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper Shipping Name Please refer to the Bill of Lading/receiving documents for up to date shipping information.

TDG Classification

TDG Proper Shipping Name Please refer to the Bill of Lading/receiving documents for up to date shipping information.

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal Clean air act (CAA) 112 regulated flammable substances: Isobutane, Propane
 CERCLA: Hazardous substances.: Isobutane, Propane, Ethyl Alcohol

State New Jersey: Isobutane, Propane, Ethyl Alcohol
 Massachusetts spill list: Isobutane, Propane, Ethyl Alcohol
 Massachusetts RTK: Isobutane, Propane, Ethyl Alcohol
 Pennsylvania RTK: Isobutane, Propane, Ethyl Alcohol

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information EPA Registration Number: 11525-30-4822

Canadian Regulations

WHMIS Classification Not controlled under WHMIS (Canada).

WHMIS Icon



Registered Product Information Not applicable.

Chemical Inventory Status All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information

Other Special Considerations MSDS Serial Range: 006-007

Version 1.01

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.