



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 11532

PRODUCT NAME: PERMA-GARD 3055 R1**USE:** Phosphatizer**SUPPLIER:**JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada**EMERGENCY PHONE:****1-800-668-7171****WHMIS CLASSIFICATION:** D2A E**CHEMICAL FAMILY:** mineral acid**TRADE NAME / SYNONYMS:** not applicable**CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Phosphoric acid	25-30	007664-38-2	LD50 1530 mg/kg	oral/rat
Nickel Nitrate	5-10	013138-45-9	not available	n/a
Zinc oxide	5-10	001314-13-2	LD50 >8437 mg/kg	oral/rat
Manganese oxide	1-5	001344-43-0	not available	n/a

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:**Gloves:** Natural rubber or neoprene**Eye:** Safety goggles**Footwear:** Not required**Respiratory:** If mists are generated, use NIOSH approved mask**Other:** Rubber apron**SPECIAL HANDLING PROCEDURES AND EQUIPMENT:** Avoid eye and skin contact. Do not breathe mist, spray or vapours.**VENTILATION REQUIREMENTS:** Local exhaust ventilation.**INCOMPATIBILITY (Material to Avoid):** Alkaline and chlorinated materials.**SPILL PROCEDURES:** Contain the spill. Do not allow the spilled product to go to drain. Neutralize with sodium bicarbonate, sodium carbonate or lime. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.**WASTE DISPOSAL:** Dispose according to municipal, provincial, and federal regulations.**STORAGE / SHIPPING REQUIREMENT:** Store in a cool dry area in a closed container.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, light green liquid**S.G. / BULK DENSITY(g/cc):** 1.377**pH:** (concentrate): 1.3**VAPOUR PRESSURE (mmHg):** not available**VAPOUR DENSITY (air=1):** not available**ODOUR THRESHOLD:** not available**BOILING POINT:** >100°C**FREEZING POINT:** not available**PERCENT VOLATILE:** 51.5%**SOLUBILITY IN WATER:** soluble**EVAPORATION RATE (water=1):** approx. 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**EYES:** Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.**SKIN:** Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.**INGESTION:** Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly.

INHALATION: Corrosive. Inhalation of spray or mist may cause severe respiratory irritation.	
LD50 (calculated): 1549	LC50 (calculated): not available
OTHER TOXIC EFFECTS: Phosphoric acid TWA 1 mg/m3, STEL 3 mg/m3; Maganese oxide TLV/TWA 0.2 mg/m3; Nickel nitrate (soluble compound as Ni) TWA 0.1 mg/m3; Zinc oxide (repirable dust) TWA 5 mg/m3	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: not available	
VI - FIRST AID MEASURES	
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.	
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.	
INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.	
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.	
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: No.	
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.	
HAZARDOUS COMBUSTION PRODUCTS: not applicable.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: Contact with soft metals.	
INCOMPATIBILITY (Material to Avoid) : Alkaline and chlorinated materials. Organic materials.	
HAZARDOUS DECOMPOSITION PRODUCTS: Contact with chlorinated materials will release chlorine gas. Contact with alkali will generate heat. Contact with soft metals forms flammable hydrogen gas. Contact with organic materials will generate heat.	
REACTIVITY: not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: RTECS	PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Industrial Division Phone (905) 829-1200
PREPARATION DATE: November 7, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	