



Material Safety Data Sheet

GC207

| National Fire Protection Association (N | NFPA) Health Health Reactivity | | Hazardous M Information (HMIS) | | Health1Fire Hazard4Reactivity0 |
|--|---|-----------|--------------------------------------|--------------------------------|---------------------------------------|
| Protective None | Specific Hazard | mergency | Off-white. Aeros | sol. See Sectio | on 9. |
| Clothing | • | verview | WARNING: PRESSURE. N | | LE. CONTENTS UNDER rritating to skin. |
| Section 1. C | hemical Product and Company Identi | ification | | | |
| Product Name | GC207 | | | Code | 38081 |
| Product Use | Industrial/Institutional: Cleaning product. | | | PMS# | 433301 |
| MSDS# | 126184001 | | | Validation Dat | e 1/10/2001 |
| U.S. Headquarters | | | | Print Date | 1/10/2001 |
| Johnson Wax Pro 8310 16th Street | fessional | | | Supersedes | 4/19/2000. |
| Sturtevant, Wiscol Phone: (888) 352- MSDS Internet Ad www.jwp.com | 2249 | | | <u>In Case of</u> Emergency | (800) 851-7145 |
| Section 2. C | omposition and Information on Ingre | dients | | | |

| Ingredients | CAS # | % by Weight | Exposure Limits | LC50/LD50 |
|-----------------------------------|------------|-------------|---|--|
| Propane | 74-98-6 | 1-5 | TWA: 1800 (mg/m ³) from OSHA (PEL) [United States] TWA: 4508 (mg/m ³) from ACGIH (TLV) [United States] | Not available. |
| Isobutane | 75-28-5 | 5-10 | Not available. | VAPOR (LC50): Acute: 0.0057 ppm 0.25 hours [Rat]. |
| Light Naphthenic Distillate | 64741-44-2 | 10-30 | Not available. | Not available. |
| Isoparaffinic Hydrocarbon Solvent | 64742-48-9 | 10-30 | Not available. | Not available. |
| Water | 7732-18-5 | 60-100 | Not available. | Not applicable. |

Section 3. Hazards Identification Routes of Entry Inhalation. Skin contact. Eye contact. Potential Acute Health Effects Eyes None known. Skin May be mildly irritating to skin. Inhalation None known. Ingestion None known. Aggravated by Overexposure: Section 11) Section 4. First Aid Measures

| Eye Contact | Rinse with plenty of running water. |
|--------------|---|
| Skin Contact | Flush immediately with plenty of water. Get medical attention if irritation occurs. |
| Inhalation | No specific first aid measures are required. |
| Ingestion | No specific first aid measures are required. |
| | |

Johnson wax PROFESSIONAL

GC207

Section 5. Fire Fighting Measures

| Flammability of the Product Flash Points | NFPA 30B Level 2 Aerosol. CLOSED CUP: <-7°C (19.4°F).(propellant) |
|--|--|
| Products of Combustion | None known. |
| Fire Fighting Media and Instructions | Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide. Fight fire from protected location or maximum possible distance. In case of fire and/or explosion do not breathe fumes |
| Special Remarks on Fire and Explosion Hazards | Aerosol product - Containers may rocket or explode in heat of fire. |

Section 6. Accidental Release Measures

| Personal Precautions | Put on appropriate personal protective equipment (see Section 8). |
|---|--|
| Environmental Precautions and Clean-up Methods | Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods. |

Section 7. Handling and Storage

| Handling | Avoid contact with skin and eyes. Avoid breathing vapors or spray mists. Use only in well-ventilated areas. Do not puncture or incinerate. Do not let product overspray on to the floor as the product's ingredients could make the floor slippery. FOR INDUSTRIAL USE ONLY. |
|----------|--|
| Storage | Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. Pressurized container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN. |

Section 8. Exposure Controls/Personal Protection

| Engineering Controls | No special ventilation requirements. General room ventilation is adequate. |
|----------------------|--|
| Personal Protection | |
| Eyes | No special requirements under normal use conditions. |
| Hands | No special requirements under normal use conditions. |
| Respiratory | No special requirements under normal use conditions. |
| Feet | No special requirements under normal use conditions. |
| Body | No special protective clothing is required. |

Section 9. Physical and Chemical Properties

| Physical State and Appearance | Liquid. (Aerosol.) |
|----------------------------------|--------------------|
| Odor | Mild. |
| Color | Off-white. |
| рН | Not available. |
| Specific Gravity | 0.8 |
| Solubility in water | Appreciable. |

Section 10. Stability and Reactivity

| Section 10. Stability and Reactivity | | |
|---|---|--|
| Stability and Reactivity | The product is stable. | |
| Conditions of Instability | None known. | |
| Incompatibility with Various Substances | None known. | |
| Hazardous Decomposition Products | When exposed to fire: Produces normal products of combustion. | |
| Hazardous Polymerization | Will not occur. | |

Material Safety Data Sheet

Johnson wax PROFESSIONAL GC207

Section 11. Toxicological Information

| Acute toxicity | ORAL (LD50) Estimated to be greater than 5000 mg/kg (rat). DERMAL (LD50) Estimated to be greater than 2000 mg/kg (rat). |
|-----------------------------|---|
| Effects of Chronic Exposure | None known. |
| Other Toxic Effects | None known. |

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information

If possible, recycle empty aerosol cans to the nearest steel recycling center. Use up package or give to someone who can. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

| DOT Proper Shipping Name | Consumer Commodity |
|-------------------------------|--------------------|
| DOT Class | ORM-D |
| DOT Special Considerations | Limited Quantity |

Section 15. Regulatory Information

| 0 | - |
|--|---|
| Reporting in this section US Regulations | is based on ingredients disclosed in Section 2 |
| Federal | Clean air act (CAA) 112 regulated flammable substances: Propane, Isobutane CERCLA: Hazardous substances.: Propane, Isobutane |
| State | New Jersey: Light Naphthenic Distillate, Propane, Isobutane, Light Naphthenic Distillate Massachusetts spill list: Propane, Isobutane Massachusetts RTK: Propane, Isobutane Pennsylvania RTK: Propane, Isobutane |
| | This product is not subject to the reporting requirements under California's Proposition 65. |
| Registered Product Information | Not applicable. |
| Chemical Inventory Status | All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory. |

Section 16. Other Information Other Special Considerations Not available. Version 1.01

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.