National Fire Protection Association (NFPA)



Specific Hazard

Hazardous Material Information System (HMIS) Health 3
Fire Hazard 0
Reactivity 0

Protective Clothing







Emergency Overview

cy Clear Red. Liquid. See Section 9.

DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED.

Section 1. Chemical Product and Company Identification			
Product Name	MR. MUSCLE CONCRETE CLEANER	Code	94488
Product Use	Industrial/Institutional: Floor care.	PMS#	433319
MSDS#	126255001	Validation Date	04/19/2000
U.S. Headquarters		Print Date	04/20/2000
Drackett Professional A Division of S.C. Johnson Commercial Markets, Inc. 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249		Supersedes In Case of Emergency	04/13/2000. (800) 851-7145

Section 2. Composition and Information on Ingredients				
Ingredients	CAS#	% by Weight	Exposure Limits	LC50/LD50
Sodium Hydroxide	1310-73-2	1-5	CEIL: 2 (mg/m³) from OSHA (PEL) [United States] STEL: 2 (mg/m³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 140-340 mg/kg [Rat]
Tetrasodium Salt of EDTA	64-02-8	1-5	Not available.	ORAL (LD50): Acute: >630 mg/kg [Rat]
Sodium silicate	1344-09-8	1-5	Not available.	ORAL (LD50): Acute: 1150 mg/kg [Rat]
Alkylphenoxy Polyethoxyethanol	26027-38-3	1-5	Not available.	ORAL (LD50): Acute: 1600-2000 mg/kg [Rat]
Sodium Xylene Sulfonate	1300-72-7	1-5	Not available.	ORAL (LD50): Acute: 2000 mg/kg [Rat]
2-Butoxyethanol	111-76-2	7-13	TWA: 120 (mg/m³) from OSHA (PEL) [United States] TWA: 97 (mg/m³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hours [Rat].
Water	7732-18-5	60-100	Not available.	Not available.

Section 3. Hazards Identification		
Routes of Entry	Inhalation. Skin contact. Eye contact.	
Potential Acute Health Effects		
Eyes	Corrosive. May cause permanent damage including blindness.	
Skin	Corrosive. May cause permanent damage.	
Inhalation	May cause irritation and corrosive effects to nose, throat and respiratory tract.	
Ingestion	Corrosive. May cause burns to mouth, throat, and stomach.	
Medical Conditions Aggravated by Overexposure:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.	
See Toxicological Information (section 11)		

Section 4. First Aid Measures		
Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.	
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.	
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.	
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.	

Section 5. Fire Fighting Measures		
Flammability of the Product Flash Points	None known. Not available.	
Products of Combustion	None known.	
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.	
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).	
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).	

Section 6. Accidental Release Measures	
Personal Precautions	Put on appropriate personal protective equipment (see Section 8).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage		
Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.	
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.	

Section 8. Exposure Controls/Personal Protection		
Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.	
Personal Protection		
Eyes	Chemical splash goggles.	
Hands	Chemical resistant gloves. Includes: Neoprene gloves. Rubber gloves.	
	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.	
Feet	Protective footwear.	
Body	If major exposure is possible, wear suitable protective clothing and footwear.	

Section 9. Physical and Chemical Properties

Physical State and

Appearance

Liquid.

Odor Mild.

Color Clear Red.

pH 12 [Basic.] (Minimum)

Specific Gravity

Boiling/Condensation Point 100°C (212°F) Melting/Freezing Point 0°C (32°F)

Solubility in water Complete.

Section 10. Stability and Reactivity		
Stability and Reactivity	The product is stable.	
Conditions of Instability	None known.	
Incompatibility with Various Substances	Reactive with acids.	
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.	
Hazardous Polymerization	Will not occur.	

Section 11. Toxicological Information	
Acute toxicity	Corrosive.
Effects of Chronic Exposure	None known.

Section 12. Ecological Information

Not available.

Other Toxic Effects

Section 13. Disposal Considerations

Waste Information Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper Corrosive liquids, n.o.s. (Sodium hydroxide , Sodium silicate)

Shipping Name

DOT Class Class 8: Corrosive material

Not available.

UN/NA UN1760
Packing Group ||

TDG Classification

TDG Proper Corrosive liquids, n.o.s. (Sodium hydroxide , Sodium silicate)

Shipping Name

TDG Class Class 8: Corrosive material

PIN/NIP UN1760
Packing Group ||

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal Clean Water Act (CWA) 311: Sodium Hydroxide

CERCLA: Hazardous substances.: Sodium Hydroxide, 2-Butoxyethanol

State New Jersey spill list: Sodium Hydroxide, 2-Butoxyethanol

New Jersey: Sodium Hydroxide, 2-Butoxyethanol

Massachusetts spill list: Sodium Hydroxide, 2-Butoxyethanol Massachusetts RTK: Sodium Hydroxide, 2-Butoxyethanol Pennsylvania RTK: Sodium Hydroxide, 2-Butoxyethanol

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Not applicable.

Information

Canadian Regulations

Canadian NPRI Canadian NPRI: Alkylphenoxy Polyethoxyethanol, 2-Butoxyethanol.

WHMIS Classification CLASS E: Corrosive liquid.

WHMIS Icon



Registered Product Not applicable.
Information

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information Other Special Considerations Version 1

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.