

PAINT, OIL & GREASE SPOTTER GEL

	, 0.12		ASE SFU		<u> </u>
National Fire Protection Association (NFPA)	Fire Haze	ard Reactivity	Hazardous Information (HMIS)		Health1Fire Hazard2Reactivity0
	Specific H	azard			
Protective None required. Clothing	~	Emer		COMBUSTI	tion 9. BLE. HARMFUL OR FATAL IF
Section 1. Chemical Proc	luct and Com	pany Identific	ation		
Product Name PAINT, OI	L & GREASE	SPOTTER GE	L	Code	13888
	titutional: Carpet			PMS#	451088
MSDS# 126332004				Validation I	Date 10/9/2001
U.S. Headquarters		Canadian Headqu	arters	Print Date	10/9/2001
Johnson Wax Professional 8310 16th Street		Johnson Wax Pro		Supersedes	10/9/2001.
Sturtevant, Wisconsin 53177-090 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com	2	100 Matheson Blvd. East, Suite 203Mississauga, Ontario L4Z 2G7In Case of		<u>In Case of</u> <u>Emergency</u>	(800) 851-7145
Section 2. Composition and Information on Ingredients					
Ingredients	CAS #	% by Weight	Exposure Lin	mits	LC50/LD50
Amorphous Silica	112945-52-5	1-5	Not available.		ORAL (LD50): Acute: 3160
Ethoxylated Alcohol Diethylene Glycol Butyl Ether Isoparaffinic Hydrocarbon Solvent	68551-12-2 112-34-5 64742-47-8	1-5 10-30 60-100	Not available. Not available. Not available.		mg/kg [Rat]. Not available. ORAL (LD50): Acute: 5660 mg/kg [Rat]. DERMAL (LD50): Acute: 2700 mg/kg [Rabbit]. ORAL (LD50): Acute: >10 mg/kg
	[Rat].			[Rat].	
Section 3. Hazards Identi	ification				
Routes of Entry Eye contact. Ingestion. Inhalation. Skin contact					
Potential Acute Health Effects					
Eyes Nor	e known.				
Skin May	v be mildly irritatii	ng to skin.			
Inhalation Nor	e known.				
Ingestion HARMFUL OR FATAL IF SWALLOWED. Aspiration into the lungs may cause chemical pneumonitis. May cause abdominal discomfort, nausea, vomiting and diarrhea.					
Medical Conditions Persons with pre-existing skin disorders may be more susceptable to irritating effects. Aggravated by Overexposure: Second Sec					
See Toxicological Information (section 11)					
Section 4. First Aid Measures					
Eye Contact Rin:	Eye Contact Rinse with plenty of running water.				
Skin Contact Flus	Flush immediately with plenty of water. Get medical attention if irritation occurs.				
Inhalation No specific first aid measures are required.					
Ingestion Do not induce vomiting! Call medical attendant, doctor, or poison control center immediately.					

PAINT, OIL & GREASE SPOTTER GEL

Johnson wax PROFESSIONAL PA

Section 5. Fire Fighting Measures		
Flammability of the Product Flash Points	COMBUSTIBLE. CLOSED CUP: 85.556°C (186°F).	
Products of Combustion	None known.	
Fire Fighting Media and Instructions	Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide.	
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8.).	
Special Remarks on Fire and Explosion Hazards	Material may burn in heat of fire. Liquid will float and may reignite on surface of water.	

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).	
Environmental Precautions and Clean-up Methods	Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods.	

Section 7. Handling and Storage

Handling	Do not taste or swallow. Avoid breathing vapors or spray mists. Use appropriate hygiene measures when handling product. Use only in well-ventilated areas. Avoid contact with skin and eyes. FOR INDUSTRIAL USE ONLY
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls No special ventilation requirements. General room ventilation is adequate.

Personal Protection

Eyes No special requirements under normal use conditions.

Hands No special requirements under normal use conditions.

Respiratory No special requirements under normal use conditions.

Feet No special requirements under normal use conditions.

Body No special protective clothing is required.

Section 9. Physical and Chemical Properties

Physical State and	Liquid. (Gel.)	
Appearance		
Odor	Fruity.	
Color	Translucent.	
рН	Not available.	
Specific Gravity	0.82	
Solubility in water	Dispersible.	

Section 10. Stability and Reactivity		
Stability and Reactivity	The product is stable.	
Conditions of Instability	Excessive heat.	
Incompatibility with Various Substances	Reactive with oxidizing agents.	
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.	
Hazardous Polymerization	Will not occur.	

Johnson wax PROFESSIONAL

Section 11. Toxicolo	gical Information		
Acute toxicity	ORAL (LD50) Estimated to be greater than 5000 mg/kg (rat).		
Effects of Chronic Exposure	None known.		
Other Toxic Effects	None known.		
Section 12. Ecologic	al Information		
Not available.			
Section 13. Disposal	Considerations		
Waste Information	Undiluted product is regulated under environmental and transportation laws as an ignitable waste. Dispose of according to all federal, state and local regulations.		
Section 14. Transpor	rt Information		
DOT Classification			
DOT Proper Shipping Name DOT Class	Please refer to the Bill of Lading/receiving documents for up to date shipping information.		
TDG Classification			
TDG Proper Shipping Name TDG Class	Please refer to the Bill of Lading/receiving documents for up to date shipping information.		
Section 15. Regulato	ry Information		
Reporting in this section US Regulations	is based on ingredients disclosed in Section 2		
Federa	I CERCLA: Hazardous substances.: Diethylene Glycol Butyl Ether		
State	e New Jersey spill list: Diethylene Glycol Butyl Ether New Jersey: Diethylene Glycol Butyl Ether Pennsylvania RTK: Diethylene Glycol Butyl Ether		
	This product is not subject to the reporting requirements under California's Proposition 65.		
Registered Product Information			
Canadian Regulations			
WHMIS Classification	Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).		
WHMIS Icon			
Registered Product Information			



Section 16. Other Information		
Other Special Considerations	Not available.	
Version	1	
Notice to Reader		

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.