3

0

0



# JP OPTIMUM LIQUID CARBON BUILD-UP REMOVER

Fire Hazard **National Fire Hazardous Material** Health **Protection Information System** Fire Hazard Health Reactivity Association (NFPA) (HMIS) Reactivity

Specific Hazard

**Protective** Clothing



Clear. Liquid. See Section 9. **Emergency** Overview

DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS.

HARMFUL OR FATAL IF SWALLOWED.

| Section 1. Chemical Product and Company Identification   |  |  |                                 |  |
|--|--|--|---------------------------------|--|
| Product Name   | JP OPTIMUM LIQUID CARBON BUILD-UP REMOVER  |  | Code                            | 7868                                   |
| <b>Product Use</b>   | Industrial/Institutional: Cleaning product. This product is intended to be diluted prior to use. |  | PMS#                            | 444547                                 |
| MSDS#  | 126441001  | 126441001  |                                 | 4/5/2001                               |
| U.S. Headquarters  |  | Canadian Headquarters  | Print Date                      | 4/5/2001                               |
| Johnson Wax Professional<br>8310 16th Street<br>Sturtevant, Wisconsin 53177-0902<br>Phone: (888) 352-2249<br>MSDS Internet Address:<br>www.jwp.com |  | Johnson Wax Professional<br>100 Matheson Blvd. East, Suite 203<br>Mississauga, Ontario L4Z 2G7<br>Phone: (905) 755-0913 or<br>(888) 746-5971 | Supersedes In Case of Emergency | No Previous Validation. (800) 851-7145 |

| Section 2. Composition and Information on Ingredients |           |             |   |   |
|---|-----------|-------------|---|---|
| Ingredients   | CAS#      | % by Weight | Exposure Limits   | LC50/LD50   |
| Potassium Hydroxide                                   | 1310-58-3 | 5-10        | CEIL: 2 mg/m³ from OSHA<br>(United States).<br>STEL: 2 mg/m³ from ACGIH<br>(United States). | ORAL (LD50): Acute: 365 mg/kg [Rat]. 273 mg/kg [Male. Rat]. |
| Sodium Silicate                                       | 1344-09-8 | 30-60       | Not available.  | Not available.  |
| Water   | 7732-18-5 | 30-60       | Not available.  | Not available.  |

| Section 3. Hazards Identification                 |  |  |
|---|--|--|
| Routes of Entry                                   | Eye contact. Skin contact Inhalation.  |  |
| <b>Potential Acute Health Effects</b>             |  |  |
| Eyes  | Corrosive. May cause permanent damage including blindness.   |  |
| Skin  | Corrosive. May cause permanent damage.   |  |
| Inhalation  | May cause irritation and corrosive effects to nose, throat and respiratory tract.  |  |
| Ingestion   | Corrosive. May cause burns to mouth, throat, and stomach.  |  |
| Medical Conditions<br>Aggravated by Overexposure: | Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects. |  |
| See Toxicological Information                     | (section 11)   |  |

| Section 4. First Aid Measures |   |  |
|-------------------------------|---|--|
| Eye Contact                   | Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.                                       |  |
| Skin Contact                  | Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.  |  |
| Inhalation                    | If breathing is difficult: Remove to fresh air. Get medical attention immediately.  |  |
| Ingestion                     | Do not induce vomiting! Immediately drink 1-2 glasses of water or milk. Never give anything by mouth to an unconscious person. Get medical attention immediately. |  |

## JP OPTIMUM LIQUID CARBON BUILD-UP REMOVER

| Section 5. Fire Fighting Measures             |   |  |
|---|---|--|
| Flammability of the Product Flash Points      | None known.<br>CLOSED CUP: >93°C (200°F).   |  |
| <b>Products of Combustion</b>                 | None known.   |  |
| Fire Fighting Media and Instructions          | Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used. |  |
| <b>Protective Clothing (Fire)</b>             | Put on appropriate personal protective equipment (see Section 8.).  |  |
| Special Remarks on Fire and Explosion Hazards | Corrosive material (See sections 8 and 10).   |  |

| Section 6. Accidental Release Measures         |  |  |
|--|--|--|
| <b>Personal Precautions</b>                    | Put on appropriate personal protective equipment (see Section 8).  |  |
| Environmental Precautions and Clean-up Methods | In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up. |  |

| Section 7. Handling and Storage |   |  |
|---------------------------------|---|--|
| Handling                        | Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY. |  |
| Storage                         | Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.   |  |

| Section 8. Exposure Controls/Personal Protection |  |  |
|--|--|--|
| <b>Engineering Controls</b>                      | Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.  |  |
| Personal Protection                              |  |  |
| Eyes   | Chemical splash goggles.   |  |
| Hands  | Long rubber gloves.  |  |
| , a  | If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. |  |
| Feet   | Protective footwear.   |  |
| Body   | Protective apron.  |  |

| Section 9. Physical and Chemical Properties |                |  |
|---|----------------|--|
| Physical State and<br>Appearance            | Liquid.        |  |
| Odor  | Odorless.      |  |
| Color                                       | Clear.         |  |
| pН  | 13.85 [Basic.] |  |
| Specific Gravity                            | 1.533          |  |
| Solubility in water                         | Complete.      |  |

| Section 10. Stability and Reactivity    |   |  |
|---|---|--|
| Stability and Reactivity                | The product is stable.  |  |
| <b>Conditions of Instability</b>        | None known.   |  |
| Incompatibility with Various Substances | Reactive with oxidizing agents, acids. Do not mix with any other chemicals or products unless specified by label. |  |
| Hazardous Decomposition Products        | When exposed to fire: Produces normal products of combustion.   |  |
| <b>Hazardous Polymerization</b>         | Will not occur.   |  |

#### JP OPTIMUM LIQUID CARBON BUILD-UP REMOVER

Section 11. Toxicological Information

Acute toxicity ORAL (LD50) Corrosive.

DERMAL (LD50) Corrosive.

Effects of Chronic Exposure None known.
Other Toxic Effects None known.

#### Section 12. Ecological Information

Not available.

#### Section 13. Disposal Considerations

Waste Information Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose

of according to all federal, state and local regulations.

#### Section 14. Transport Information

DOT Classification

DOT Proper

Corrosive liquid, basic, inorganic, n.o.s. ( Potassium hydroxide , Sodium silicate )

**Shipping Name** 

DOT Class Class 8: Corrosive material

UN/NA UN3266
Packing Group II

DOT Special Limited Quantity

Considerations

**Shipping Name** 

TDG Classification

TDG Proper Corrosive liquid, basic, inorganic, n.o.s. ( Potassium hydroxide , Sodium silicate )

TDG Class Class 8: Corrosive material

PIN/NIP UN3266

Packing Group ||

TDG Special Considerations

pecial Limited Quantity

## Section 15. Regulatory Information

#### Reporting in this section is based on ingredients disclosed in Section 2

**US Regulations** 

Federal Clean Water Act (CWA) 311: Potassium hydroxide

CERCLA: Hazardous substances.: Potassium hydroxide

State New Jersey spill list: Potassium hydroxide

New Jersey: Potassium hydroxide

Massachusetts spill list: Potassium hydroxide Massachusetts RTK: Potassium hydroxide Pennsylvania RTK: Potassium hydroxide

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Not applicable.

Information

Canadian Regulations


WHMIS Classification CLASS E: Corrosive liquid.

WHMIS Icon



Registered Product Not applicable.

Information





## JP OPTIMUM LIQUID CARBON BUILD-UP REMOVER

**Chemical Inventory Status** 

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

| Section 16. Other Information   |                |  |
|---------------------------------|----------------|--|
| Other Special<br>Considerations | Not available. |  |
| Version                         | 1              |  |

#### **Notice to Reader**

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.