Fire Hazard **National Fire Hazardous Material** Health 0 **Protection Information System** Fire Hazard 4 Health Reactivity Association (NFPA) (HMIS) Reactivity 0 Specific Hazard Protective None required. Clear Aerosol. See Section 9. Emergency CAUTION: CONTENTS UNDER PRESSURE. Clothing Overview

| Section 1. Chemical Product and Company Identification | | | |
|---|---|-------------------------|----------------|
| Product Name | PLEDGE ELECTRONICS CLEANING & DUSTING SPRAY | Code | 94323 |
| Product Use | Industrial/Institutional: Cleaning product. | PMS# | 436676 |
| MSDS# | 126499002 | Validation Date | 5/28/2002 |
| U.S. Headquarters | | Print Date | 5/28/2002 |
| Drackett Professional | | Supersedes | 5/28/2002. |
| A Division of S.C. Johnson Commercial Markets, Inc. 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 | | In Case of Emergency | (800) 851-7145 |

| Section 2. Composition and Information on Ingredients | | | | |
|---|-----------|-------------|--|---|
| Ingredients | CAS# | % by Weight | Exposure Limits | LC50/LD50 |
| Ammonium Hydroxide | 1336-21-6 | <0.5 | Not available. | ORAL (LD50): Acute: 350 mg/kg [Rat]. |
| 2-Butoxyethanol | 111-76-2 | 1-5 | TWA: 120 (mg/m³) from OSHA (PEL) [United States] TWA: 97 (mg/m³) from ACGIH (TLV) [United States] | ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hours [Rat]. |
| Isobutane | 75-28-5 | 3-7 | Not available. | VAPOR (LC50): Acute: 0.0057 ppm 0.25 hours [Rat]. |
| Isopropyl Alcohol | 67-63-0 | 10-30 | TWA: 980 STEL: 1225 (mg/m³) from OSHA (PEL) [United States] TWA: 983 STEL: 1230 (mg/m³) from ACGIH (TLV) [United States] | ORAL (LD50): Acute: 5045 mg/kg [Rat]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit]. VAPOR (LC50): Acute: 16000 ppm 8 hours [Rat]. |
| Water | 7732-18-5 | 60-100 | Not available. | Not available. |

| Section 3. Hazards Identification | | |
|---|--------------------------|--|
| Routes of Entry | Inhalation. Eye contact. | |
| Potential Acute Health Effects | | |
| Eyes | None known. | |
| Skin | None known. | |
| Inhalation | None known. | |
| Ingestion | None known. | |
| Medical Conditions Aggravated by Overexposure: | None known. | |
| See Toxicological Information (| (section 11) | |

| Section 4. First Aid Measures | | |
|-------------------------------|--|--|
| Eye Contact | Rinse with plenty of running water. | |
| Skin Contact | Rinse with plenty of running water. | |
| Inhalation | No specific first aid measures are required. | |
| Ingestion | No specific first aid measures are required. | |

| Section 5. Fire Fighting Measures | | |
|---|---|--|
| Flammability of the Product Flash Points | NFPA 30B Level 1 Aerosol. < 7°C (propellant). | |
| Products of Combustion | None known. | |
| Fire Fighting Media and Instructions | Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide. Fight fire from protected location or maximum possible distance. In case of fire and/or explosion do not breathe fumes. | |
| Protective Clothing (Fire) | Put on appropriate personal protective equipment (see Section 8.). | |
| Special Remarks on Fire and Explosion Hazards | Aerosol product - Containers may rocket or explode in heat of fire. | |

| Section 6. Accidental Release Measures | | |
|--|--|--|
| Personal Precautions | utions Put on appropriate personal protective equipment (see Section 8.). | |
| Environmental Precautions and Clean-up Methods | Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods. | |

| Section 7. Handling and Storage | | |
|---------------------------------|---|--|
| Handling | Do not puncture or incinerate. FOR INDUSTRIAL USE ONLY | |
| Storage | Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. Do not puncture or incinerate. Pressurized container: protect from sunlight and do not expose to temperature exceeding 120°F (50°C). Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN. | |

| Section 8. Exposure Controls/Personal Protection | | |
|--|--|--|
| Engineering Controls | No special ventilation requirements. General room ventilation is adequate. | |
| Personal Protection | | |
| Ey | No special requirements under normal use conditions. | |
| Hand | ds No special requirements under normal use conditions. | |
| Respirato | ry No special requirements under normal use conditions. | |
| Fe | et No special requirements under normal use conditions. | |
| Boo | dy No special protective clothing is required. | |

| Section 9. Physical and Chemical Properties | | |
|---|--------------------|--|
| Physical State and Appearance | Liquid. (Aerosol.) | |
| Odor | Fresh. | |
| Color | Clear | |
| рН | 10.7 [Basic.] | |
| Specific Gravity | 0.95 | |
| Boiling/Condensation Point | 100°C (212°F) | |
| Melting/Freezing Point | 0°C (32°F) | |
| Solubility in water | Complete. | |

| Section 10. Stability and Reactivity | | |
|--|---|--|
| Stability and Reactivity | The product is stable. | |
| Conditions of Instability | Excessive heat. | |
| Incompatibility with Various Substances | Not available. | |
| Hazardous Decomposition Products | When exposed to fire: Produces normal products of combustion. | |
| Hazardous Polymerization | Will not occur. | |

| Section 11. Toxicological Information | | |
|---------------------------------------|---|--|
| Acute toxicity | ORAL (LD50) Estimated to be greater than 5000 mg/kg (rat). DERMAL (LD50) Estimated to be greater than 2000 mg/kg (rat). | |
| Effects of Chronic Exposure | None known. | |
| Other Toxic Effects | Not available. | |

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information If possible, recycle empty aerosol cans to the nearest steel recycling center. Use up package or give to

someone who can. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper Shipping Name Please refer to the Bill of Lading/receiving documents for up to date shipping information.

TDG Classification

TDG Class Not applicable.

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal SARA 313 toxic chemical notification and release reporting: Isopropyl Alcohol

Clean air act (CAA) 112 regulated flammable substances: Isobutane

CERCLA: Hazardous substances.: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane

State New Jersey spill list: Isopropyl Alcohol, 2-Butoxyethanol

New Jersey: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane

Massachusetts spill list: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane Massachusetts RTK: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane Pennsylvania RTK: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information Not applicable.

Canadian Regulations

Canadian NPRI Not applicable.
WHMIS Classification Not applicable.

WHMIS Icon

Registered Product Not applicable.

Information

Chemical Inventory Status All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

| Section 16. Other Information | | |
|---------------------------------|-----------------------------|--|
| Other Special Considerations | MSDS Serial Range: 001-002. | |
| Version | 1.01 | |
| | | |

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.