



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 1291

PRODUCT NAME: **FRYER CLEANER & DEGREASER D34**

USE: Grease Remover

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: D2B

CHEMICAL FAMILY: Surfactant/Solvent

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Potassium carbonate	5-10	000584-08-7	LD50 1870 mg/kg	oral/rat
Dipropylene glycol methyl ether	3-7	034590-94-8	LD50 5660 mg/kg	oral/rat
Dipropylene glycol monobutyl ether	3-7	029911-28-2	LD50 4400 mg/kg	oral/rat
Sodium metasilicate	3-7	006834-92-0	LD50 1153 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Neoprene or Nitrile

Eye: safety glasses

Footwear: not required

Respiratory: not required

Other: not required

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): Oxidizing materials.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Red liquid

S.G. / BULK DENSITY(g/cc): 1.1

pH: 13.5

VAPOUR PRESSURE (mmHg): not available

VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD: not available

BOILING POINT: approx. 100°C

FREEZING POINT: approx. 0°C

PERCENT VOLATILE: 80%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): approx. 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause severe irritation.

SKIN: May cause severe irritation.

INGESTION: May cause severe irritation of the digestive tract.

INHALATION: No serious or irreversible effects expected.

LD50 (calculated): 11,540 mg/kg		LC50 (calculated): not applicable	
OTHER TOXIC EFFECTS: TLV - Dipropylene Glycol Methyl Ether TWA: 606 mg/m3; STEL: 909 mg/m3			
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known			
VI - FIRST AID MEASURES			
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.		
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.		
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.		
INHALATION:	Remove patient to fresh air.		
VII - FIRE AND EXPLOSION DATA			
FLAMMABLE: No			
FLASH POINT, °C: none		AUTO IGNITION TEMPERATURE, °C: N/Ap	
EXTINGUISHING MEDIA: Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other []			
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.			
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.			
EXPLOSIVE SENSITIVITY TO: not applicable			
VIII - REACTIVITY DATA			
STABILITY: Stable [X] Unstable []			
CONDITIONS TO AVOID: not applicable			
INCOMPATIBILITY (Material to Avoid) : Oxidizing materials.			
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with oxidizing materials.			
REACTIVITY: not dangerously reactive			
IX - MSDS PREPARATION			
SOURCES USED: RTECS, Supplier's MSDS.		PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200	
PREPARATION DATE: April 15, 2003			
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.			