



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 95011

PRODUCT NAME: SUNLIGHT POT & PAN LIQUID

USE: Manual Warewashing Detergent

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: B3 D2B

CHEMICAL FAMILY: surfactant

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Sodium dodecylbenzene sulphonate	10-30	025155-30-0	LD50 1260 mg/kg	oral/rat
Sodium lauryl ether sulphate	5-10	009004-82-4	LD50 1600 mg/kg	oral/rat
Ethanol	1-5	000064-17-5	LD50 7060 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: not required

Eye: not required

Footwear: not required

Respiratory: not required

Other: not required

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: not applicable

VENTILATION REQUIREMENTS: General ventilation

INCOMPATIBILITY (Material to Avoid): Contact with cationic materials causes inactivation.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool, dry area in a closed container. Avoid freezing.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear yellow liquid - lemon scent

S.G. / BULK DENSITY(g/cc): 1.06

pH: 7.0 ± 1.0

VAPOUR PRESSURE (mmHg): not available

VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD: not available

BOILING POINT: approx. 100°C

FREEZING POINT: approx. 2°C

PERCENT VOLATILE: approx. 66%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause irritation.

SKIN: Repeated or prolonged contact may result in irritation.

INGESTION: May cause irritation of the digestive tract.

INHALATION: No serious or irreversible effects expected.

LD50 (calculated): 5546 mg/kg

LC50 (calculated): not applicable

OTHER TOXIC EFFECTS: TLV (Ethanol) TWA 1000 ppm, 1880 mg/m3	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eye lids open while rinsing. Contact a physician immediately.
SKIN:	Flush affected area thoroughly with water.
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious person. Do not induce vomiting. Contact a physician immediately.
INHALATION:	Remove patient to fresh air. Get medical attention for any breathing difficulty.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: Yes, combustible if heated.	
FLASH POINT, °C: 56.7	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: not applicable	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, sulphur.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [X] Unstable []	
CONDITIONS TO AVOID: high temperature	
INCOMPATIBILITY (Material to Avoid) : Oxidizing materials	
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with oxidizing materials.	
REACTIVITY: Not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: RTECS, MSDS	PREPARED BY: JohnsonDiversey Canada. Inc. Regulatory Department Institutional Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	