



MATERIAL SAFETY DATA SHEET



| I - PRODUCT IDENTIFICATION AND USE MSDS ID: 2319 | | | | | |
|---|------------|---|---------------------------------------|------------------------------------|----------------------|
| PRODUCT NAME: SUNLIGHT WINDOW CLEANER | | | | | |
| USE: Window Cleaner | | | | | |
| SUPPLIER: JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada | | EMERGENCY PHONE: 1-800-668-7171 | | | |
| WHMIS CLASSIFICATION: B3 D2B CHEMICAL FAMILY: Alkali/Solvent | | TRADE NAME / SYNONYMS: not applicable CHEMICAL NAME: not applicable | | | |
| II - HAZARDOUS INGREDIENTS | | | | | |
| HAZARDOUS INGREDIENT | % w/w | 1 | CAS # | LD50 / LC50 | Route / Species |
| Isopropanol Dipropylene glycol methyl ether | 3-7 1-5 | | 000067-63-0 034590-94-8 | LD50 5045 mg/kg LD50 5660 mg/kg | oral/rat oral/rat |
| III - HANDLING AND DISPOSAL PROCEDURES | | | | | |
| PERSONAL PROTECTIVE EQUIPMENT: Gloves: not required Eye: not required Footwear: not required Respiratory: If mists are generated, use NIOSH approved mask Other: not required SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye contact. Do not breathe mist, spray or vapours. Do not expose to heat, spark or open flame. VENTILATION REQUIREMENTS: general ventilation INCOMPATIBILITY (Material to Avoid): Oxidizing materials, chlorinated materials. SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. | | | | | |
| WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations. | | | | | |
| STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. | | | | | |
| IV - PHYSICAL PROPERTIES | | | | | |
| APPEARANCE / ODOUR: Clear yellow liquid, mild ammoniacal odour | | | | | |
| .G. / BULK DENSITY(g/cc): 0.99 | | pH: 10.5 ± 0.5 | | | |
| VAPOUR PRESSURE (mmHg): not available | | VAPOUR DENSITY (air=1): not applicable | | | |
| ODOUR THRESHOLD: not applicable | | BOILING POINT: approx. 100°C | | | |
| FREEZING POINT: -1°C | | PERCENT VOLATILE: approx. 99% | | | |
| SOLUBILITY IN WATER: Soluble | | | EVAPORATION RATE (water=1): approx. 1 | | |
| V - TOXICOLOGICAL PROPERTIES | | | | | |
| EFFECTS OF ACUTE EXPOSURE TO MATERIAL: EYES: May cause severe irritation. SKIN: Repeated or prolonged contact may result in irritation. INGESTION: May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly. | | | | | |
| INHALATION: Breathing spray or mist may cause respiratory irritation. Ex LD50 (calculated): 79,612 mg/kg | | LC50 (calculated): not applicable | | | |

| OTHER TOXIC EFFECTS: TLV (Isopropanol) TWA 400 ppm (520 mg/m3) | | | | | | |
|---|--|--|--|--|--|--|
| EFFECTS OF CHRONIC none known EXPOSURE TO MATERIAL: | | | | | | |
| VI - FIRST AID MEASURES | | | | | | |
| EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately. | | | | | | |
| SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician. | | | | | | |
| INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately. | | | | | | |
| INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty. | | | | | | |
| VII - FIRE AND EXPLOSION DATA | | | | | | |
| FLAMMABLE: Yes, combustible if heated. | | | | | | |
| FLASH POINT, °C: 45°C | AUTO IGNITION TEMPERATURE,°C: N/A | | | | | |
| EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [] Other [] | | | | | | |
| SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus. | | | | | | |
| HAZARDOUS COMBUSTION PRODUCTS: Ammonia. Oxides of carbon. | | | | | | |
| EXPLOSIVE SENSITIVITY TO: not applicable | | | | | | |
| VIII - REACTIVITY DATA | | | | | | |
| STABILITY: Stable [X] Unstable [] | | | | | | |
| CONDITIONS TO AVOID: high temperature | | | | | | |
| INCOMPATIBILITY (Material to Avoid) : Chlorinated materials, ox | kidizing materials. | | | | | |
| HAZARDOUS DECOMPOSITION PRODUCTS: Heat on contact with strong oxidizers. Chloramines on contact with chlorinated materials. Nitrogen oxides. | | | | | | |
| REACTIVITY: not dangerously reactive | | | | | | |
| IX - MSDS PREPARATION | | | | | | |
| SOURCES USED: RTECS | PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department | | | | | |
| PREPARATION DATE: April 15, 2003 | Institutional Division Phone (905) 829-1200 | | | | | |
| Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use. | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |