

MATERIAL SAFETY DATA SHEET



MSDS ID: 2494

I - PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: R3 NEUTRAL GLASS & MULTI SURFACE CLEANER

USE: Glass Cleaner

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: B3 D2B TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: Solvent/Surfactant CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Isopropanol Alcohol	10-30	000067-63-0	LD50 5045 mg/kg	oral/rat
Propylene glycol monomethyl ether	10-30	000107-98-2	LD50 5660 mg/kg	oral/rat
Ammonium Lauryl Ether Sulphate	1-5	032612-48-9	LD50 630 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: not required Eye: not required Footwear: not required

Respiratory: If mists are generated, use NIOSH approved Other: not required

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye contact. Do not breathe mist, spray or vapours. Do not expose to heat,

spark or open flame.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): not applicable

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear blue liquid, pleasant odour

S.G. / BULK DENSITY(g/cc): 0.97 pH: (Concentrate): 7.0

VAPOUR PRESSURE (mmHg): not available VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD:not availableBOILING POINT:approx. 63°C

FREEZING POINT: -1°C PERCENT VOLATILE: approx. 98%

SOLUBILITY IN WATER: Soluble EVAPORATION RATE (water=1): <1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause irritation.

SKIN: Repeated or prolonged contact may result in irritation.

INGESTION: May cause severe irritation of the digestive tract.

INHALATION: Breathing spray or mist may cause respiratory irritation. Excessive exposure may cause dizziness.

LD50 (calculated): 12,493 mg/kg LC50 (calculated): not applicable

OTHER TOXIC EFFECTS: TLV-TWA (Isopropyl Alcohol) 520 mg/m3; TLV (Propylene Glycol Methyl Ether) 25 ppm ceiling

EFFECTS OF CHRONIC

EXPOSURE TO MATERIAL:

VI - FIRST AID MEASURES

EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.

SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.

INGESTION: Drink large volumes of water. Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a

physician.

INHALATION: Remove patient to fresh air.

VII - FIRE AND EXPLOSION DATA

FLAMMABLE: Yes, combustible if heated.

FLASH POINT, °C: 43° (Pensky-Martens) **AUTO IGNITION TEMPERATURE,°C:** N/Ap

EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, sulphur.

EXPLOSIVE SENSITIVITY TO: not applicable

VIII - REACTIVITY DATA

STABILITY: Stable [X] Unstable []

CONDITIONS TO AVOID: high temperature

INCOMPATIBILITY (Material to Avoid): not applicable

HAZARDOUS DECOMPOSITION PRODUCTS: not applicable

April 15, 2003

REACTIVITY: not dangerously reactive

PREPARATION DATE:

context of the intended use.

IX - MSDS PREPARATION

PREPARED BY: SOURCES USED: RTECS, RM MSDS JohnsonDiversey Canada, Inc.

> Regulatory Department Institutional Division Phone (905) 829-1200

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific