



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 2495

PRODUCT NAME: R4 FURNITURE POLISH

USE: Furniture Polish

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: D2B

CHEMICAL FAMILY: Solvent/oil

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Hydrotreated heavy naptha	3-7	064742-48-9	LD50 >5000 mg/kg	oral/rat
Alcohol ethoxylate	0.5- 1.5	068439-46-3	LD50 1400 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: natural rubber, neoprene or nitrile

Eye: safety glasses

Footwear: not required

Respiratory: If mists are generated, use NIOSH approved mask

Other: not required

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Do not breathe spray.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): oxidizing materials and reducing agents

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Avoid freezing.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Milky white liquid

S.G. / BULK DENSITY(g/cc): 0.98

pH: 6.0 ± 0.5

VAPOUR PRESSURE (mmHg): not available

VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD: not available

BOILING POINT: not available

FREEZING POINT: not available

PERCENT VOLATILE: approx. 84%

SOLUBILITY IN WATER: dispersable

EVAPORATION RATE (water=1): not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause irritation.

SKIN: Repeated or prolonged contact may result in irritation.

INGESTION: May cause severe irritation of the digestive tract.

INHALATION: Inhalation of spray or mist may cause irritation of the respiratory tract.

LD50 (calculated): >58,333 mg/kg

LC50 (calculated): not applicable

OTHER TOXIC EFFECTS: TLV (hydrotreated heavy naphtha) 300 ppm	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician
INHALATION:	Remove patient to fresh air.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: No	
FLASH POINT, °C: >93.3°C	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water [] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [X] Unstable []	
CONDITIONS TO AVOID: High temperatures, freezing.	
INCOMPATIBILITY (Material to Avoid) : oxidizing materials and reducing agents	
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with oxidizing materials.	
REACTIVITY: not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: RTECS, Supplier MSDS	PREPARED BY: JohnsonDiversey Canada. Inc. Regulatory Department Institutional Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	