

MATERIAL SAFETY DATA SHEET



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 2673

PRODUCT NAME: DUJET E

USE: Felt Conditioner

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: E TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: caustic alkali CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Potassium hydroxide	3-7	001310-58-3	LD50 273 mg/kg	oral/rat
Alkyl polyoxylethylene gylcol ether	1-5	068439-63-9	LD50 1400 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: natural rubber or neoprene Eye: safety glasses Footwear: not required

Respiratory: If mists are generated, use NIOSH approved **Other:** not required

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. Do not breathe mist or spray.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): Acidic materials, aluminum.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN1760

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear red liquid

S.G. / BULK DENSITY(g/cc): 1.06 pH: (10% Solution): 12.8 ± 0.5

VAPOUR PRESSURE (mmHg): not applicable VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not applicable **BOILING POINT:** 101°C

FREEZING POINT: 2°C PERCENT VOLATILE: 85%

SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

INGESTION: Corrosive. May cause severe irritation of the digestive tract.

INHALATION: Corrosive. Breathing mist may cause respiratory irritation.

LD50 (calculated): 4200 mg/kg LC50 (calculated): not available

OTHER TOXIC EFFECTS: Potassium Hydroxide TLV-CL 2 mg/m3 **EFFECTS OF CHRONIC** none known **EXPOSURE TO MATERIAL:** VI - FIRST AID MEASURES EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately. SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician. INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately. INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty. VII - FIRE AND EXPLOSION DATA FLAMMABLE: No FLASH POINT, °C: not applicable **AUTO IGNITION TEMPERATURE,°C:** N/App. **EXTINGUISHING MEDIA:** Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other [] SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus. **HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon. **EXPLOSIVE SENSITIVITY TO:** not applicable **VIII - REACTIVITY DATA** STABILITY: Stable [X] Unstable [] **CONDITIONS TO AVOID:** not applicable INCOMPATIBILITY (Material to Avoid): Acidic materials, aluminum. HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with acids. Contact with aluminum releases hydrogen gas. REACTIVITY: not dangerously reactive IX - MSDS PREPARATION SOURCES USED: **RTECS** PREPARED BY: JohnsonDiversev Canada. Inc. Regulatory Department Industrial Division PREPARATION DATE: April 15, 2003 Phone (905) 829-1200 Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.