

MATERIAL SAFETY DATA SHEET



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 2695 PRODUCT NAME: DUSOFT 120 USE: Pulp and Paper Softener SUPPLIER: **EMERGENCY PHONE:** JohnsonDiversey Canada, Inc. 1-800-668-7171 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada WHMIS CLASSIFICATION: D2B TRADE NAME / SYNONYMS: not applicable CHEMICAL FAMILY: Surfactant **CHEMICAL NAME:** Imidazoline **II - HAZARDOUS INGREDIENTS** HAZARDOUS INGREDIENT % w/w CAS# LD50 / LC50 **Route / Species** None **III - HANDLING AND DISPOSAL PROCEDURES** PERSONAL PROTECTIVE EQUIPMENT: Gloves: natural rubber Eye: safety glasses Footwear: not required Respiratory: as required Other: not required SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. VENTILATION REQUIREMENTS: General ventilation. INCOMPATIBILITY (Material to Avoid): Strong acids and oxidizers. SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water. WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations. STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. **IV - PHYSICAL PROPERTIES** APPEARANCE / ODOUR: Light tan emulsion S.G. / BULK DENSITY(g/cc): 0.98 7.4 ± 0.5 VAPOUR PRESSURE (mmHg): not available VAPOUR DENSITY (air=1): not applicable ODOUR THRESHOLD: not applicable **BOILING POINT:** approx. 100°C FREEZING POINT: approx. 0°C PERCENT VOLATILE: approx. 90% SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): approx. 1 **V - TOXICOLOGICAL PROPERTIES EFFECTS OF ACUTE EXPOSURE TO MATERIAL:** EYES: May cause irritation. May cause temporary or permanent damage if not treated promptly. SKIN: Repeated or prolonged contact may result in irritation. INGESTION: May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly. INHALATION: Breathing spray or mist may cause respiratory irritation. LD50 (calculated): not available LC50 (calculated): OTHER TOXIC EFFECTS: None known.

1 of 2

EFFECTS OF CHRONIC None known. **EXPOSURE TO MATERIAL: VI - FIRST AID MEASURES** EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately. SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician. INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately. INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty. VII - FIRE AND EXPLOSION DATA FLAMMABLE: No FLASH POINT, °C: **AUTO IGNITION TEMPERATURE,°C:** not applicable N/App. **EXTINGUISHING MEDIA:** Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other [x] SPECIAL FIRE FIGHTING PROCEDURES: None HAZARDOUS COMBUSTION PRODUCTS: not applicable. **EXPLOSIVE SENSITIVITY TO:** not applicable **VIII - REACTIVITY DATA** STABILITY: Unstable [] Stable [x] **CONDITIONS TO AVOID:** high temperature INCOMPATIBILITY (Material to Avoid): Strong acids and oxidizing materials Carbon dioxide, carbon monoxide. HAZARDOUS DECOMPOSITION PRODUCTS: REACTIVITY: not dangerously reactive. IX - MSDS PREPARATION PREPARED BY: SOURCES USED: **MSDS** JohnsonDiversey Canada, Inc. Regulatory Department

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.

Industrial Division

Phone (905) 829-1200

PREPARATION DATE:

April 15, 2003