



MATERIAL SAFETY DATA SHEET



I - PRODUC		CATI	ON AND USE	MSDS	ID: 2918771
PRODUCT NAME: VEHICLE CLEANER					
USE: Liquid truck wash					
SUPPLIER:			EMERGENCY PHONE:		
JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada		1-800-668-7171			
WHMIS CLASSIFICATION: E CHEMICAL FAMILY: Caustic alkali		TRADE NAME / SYNONYMS: not applicable CHEMICAL NAME: not applicable			
II - HA	ZARDOUS	INGF	REDIENTS		
HAZARDOUS INGREDIENT	% w/w		CAS #	LD50 / LC50	Route / Species
Sodium hydroxide Tetrasodium EDTA	0.1-1 1-5		001310-73-2 000064-02-8	LDIo 500 mg/kg LD50 3200 mg/kg	oral/rat oral/rat
Sodium silicate	0.1-1		001344-09-8	LD50 3300 mg/kg	oral/rat
III - HANDLING	AND DISF	POSA	L PROCEDURES		
mask SPECIAL HANDLING PROCEDURES AND EQUIPMENT: VENTILATION REQUIREMENTS: general ventilation INCOMPATIBILITY (Material to Avoid): Strong acids, stron SPILL PROCEDURES: Contain the spill. Do not allow the s Sweep or scoop up material for disp WASTE DISPOSAL: Dispose according to municipal, province STORAGE / SHIPPING REQUIREMENT: Store in a cool dry	ng aoxidizers. pilled product posal. Wash s cial, and feder	to go to pill area al regula	a with large volumes of	ak up with absorbent cla	
IV - Pł	HYSICAL F	PROP	ERTIES		
APPEARANCE / ODOUR: Clear liquid, Mild odour					
S.G. / BULK DENSITY(g/cc): 1.16		pH: (concentrate): 13.5			
VAPOUR PRESSURE (mmHg): 17.5 @ 20°C		VAPOUR DENSITY (air=1): not available			
ODOUR THRESHOLD: not available		BOILING POINT: approx. 100°C			
FREEZING POINT: 0°C		PERCENT VOLATILE: 80%			
SOLUBILITY IN WATER: soluble		EVAPORATION RATE (water=1): <1			
V - TOXIC	COLOGICA	AL PR	OPERTIES		
EFFECTS OF ACUTE EXPOSURE TO MATERIAL:EYES:Corrosive. May cause temporary or permanentSKIN:Corrosive. May cause severe irritation.INGESTION:Corrosive. May cause severe irritation of the digINHALATION:Breathing spray or mist may cause respiratory	gestive tract.	t treated	d promptly.		

LD50 (calculated): >5,000 mg/kg	LC50 (calculated):					
OTHER TOXIC EFFECTS: TLV: TWA 2 mg/m3 (sodium hydroxide)						
EFFECTS OF CHRONIC None known. EXPOSURE TO MATERIAL:						
VI - FIRST AID MEASURES						
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.						
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.						
INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.						
INHALATION: Remove patient to fresh air. VII - FIRE AND EXPLOSION DATA						
FLAMMABLE: not applicable						
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE,°C: N/App.					
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []						
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.						
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, nitrogen and sulfur.						
EXPLOSIVE SENSITIVITY TO: not applicable						
VIII - REACTIVITY DATA						
STABILITY: Stable [x] Unstable []						
CONDITIONS TO AVOID: not applicable						
INCOMPATIBILITY (Material to Avoid) : Strong acids, strong oxid						
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on co	ontact with acids.					
REACTIVITY: not dangerously reactive.						
IX - MSDS PREPARATION						
SOURCES USED: RTECS, ChemInfo.	PREPARED BY: JohnsonDiversey Canada, Inc.					
	- Regulatory Department Industrial Division					
PREPARATION DATE: April 15, 2003	Phone (905) 829-1200					
Information on this form is furnished in compliance with the Regulations res- not to be used for any other purpose, nor is it to be reproduced or published person or property resulting from any use of the material if reasonable safet assumes no responsibility for injury to any person or property resulting from procedures are followed. Each user assumes the risk in his use of the material context of the intended use.	d. JohnsonDiversey Canada assumes no responsibility for injury to any ty procedures are not adhered to. In addition, JohnsonDiversey Canada n any abnormal use or theft of the material, even if reasonable safety					