

MATERIAL SAFETY DATA SHEET



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 2918801

1-800-668-7171

PRODUCT NAME: HEAVY DUTY VEHICLE CLEANER 695

USE: Heavy duty vehicle cleaner

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc. 2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

WHMIS CLASSIFICATION: E TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: Caustic alkali CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Sodium hydroxide	5-10	001310-73-2	LDIo 500 mg/kg	oral/rat
Tetrasodium EDTA	1-5	000064-02-8	LD50 3200 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Natural rubber or neoprene Eye: safety goggles Footwear: Rubber boots

Respiratory: If mists are generated, use NIOSH approved Other: rubber apron

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. Do not breathe mist or spray.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): Strong acids, strong aoxidizers.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

Sweep or scoop up material for disposal. Wash spill area with large volumes of water. Wear protective clothing.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Avoid freezing. UN1824

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear liquid, Mild odour

S.G. / BULK DENSITY(g/cc): 1.16 pH: (concentrate): 13.5

VAPOUR PRESSURE (mmHg): 17.5 @ 20°C VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD: not available BOILING POINT: approx. 100°C

FREEZING POINT: 0°C PERCENT VOLATILE: 80%

SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): <1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause temporary or permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation.

INGESTION: Corrosive. May cause severe irritation of the digestive tract.

INHALATION: Breathing spray or mist may cause respiratory irritation.

LD50 (calculated): 6154 mg/kg LC50 (calculated):

OTHER TOXIC EFFECTS: TLV: TWA 2 mg/m3 (sodium hydroxide) **EFFECTS OF CHRONIC** None known. **EXPOSURE TO MATERIAL: VI - FIRST AID MEASURES** EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately. SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician. INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately. INHALATION: Remove patient to fresh air. VII - FIRE AND EXPLOSION DATA FLAMMABLE: not applicable FLASH POINT, °C: not applicable **AUTO IGNITION TEMPERATURE,°C:** N/App. **EXTINGUISHING MEDIA:** Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other [] SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus. **HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon, nitrogen and sulfur. **EXPLOSIVE SENSITIVITY TO:** not applicable **VIII - REACTIVITY DATA** STABILITY: Stable [x] Unstable [] **CONDITIONS TO AVOID:** not applicable INCOMPATIBILITY (Material to Avoid): Strong acids, strong oxidizers. HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with acids. REACTIVITY: not dangerously reactive. IX - MSDS PREPARATION

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific

PREPARED BY:

JohnsonDiversev Canada. Inc. Regulatory Department Industrial Division

Phone (905) 829-1200

SOURCES USED:

PREPARATION DATE:

context of the intended use.

RTECS, ChemInfo.

April 15, 2003