



I - PRODUCT IDENTIFICATION AND USE				MSDS: 2979486	
PRODUCT NAME: SUNLIGHT POT & PAN PRO FORMULA LIQUID					
USE: Manual Warewashing Detergent					
SUPPLIER: JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada			EMERGENCY PHONE: 1-800-668-7171		
WHMIS CLASSIFICATION: B3 D2B CHEMICAL FAMILY: surfactant			TRADE NAME / SYNONYMS: not applicable CHEMICAL NAME: not applicable		
II - HAZARDOUS INGREDIENTS					
HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species	
Sodium dodecylbenzene sulphonate	10-30	025155-30-0	LD50 1260 mg/kg	oral/rat	
Sodium lauryl ether sulphate	5-10	009004-82-4	LD50 1600 mg/kg	oral/rat	
Ethanol	1-5	000064-17-5	LD50 7060 mg/kg	oral/rat	
III - HANDLING AND DISPOSAL PROCEDURES					
PERSONAL PROTECTIVE EQUIPMENT: Gloves: not required Eye: not required Footwear: not required Respiratory: not required Other: not required					
SPECIAL HANDLING PROCEDURES AND EQUIPMENT: not applicable					
VENTILATION REQUIREMENTS: General ventilation					
INCOMPATIBILITY (Material to Avoid): Contact with cationic materials causes inactivation.					
SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.					
WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.					
STORAGE / SHIPPING REQUIREMENT: Store in a cool, dry area in a closed container. Avoid freezing.					
IV - PHYSICAL PROPERTIES					
APPEARANCE / ODOUR: Clear yellow liquid - lemon scent					
S.G. / BULK DENSITY(g/cc): 1.06			pH: 7.0 ± 1.0		
VAPOUR PRESSURE (mmHg): not available			VAPOUR DENSITY (air=1): not available		
ODOUR THRESHOLD: not available			BOILING POINT: approx. 100°C		
FREEZING POINT: approx. 2°C			PERCENT VOLATILE: approx. 66%		
SOLUBILITY IN WATER: soluble			EVAPORATION RATE (water=1): not available		
V - TOXICOLOGICAL PROPERTIES					
EFFECTS OF ACUTE EXPOSURE TO MATERIAL: EYES: May cause irritation. SKIN: Repeated or prolonged contact may result in irritation. INGESTION: May cause irritation of the digestive tract.					

INHALATION: No serious or irreversible effects expected.	
LD50 (calculated): 5546 mg/kg	LC50 (calculated): not applicable
OTHER TOXIC EFFECTS: TLV (Ethanol) TWA 1000 ppm, 1880 mg/m3	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known	
VI - FIRST AID MEASURES	
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eye lids open while rinsing. Contact a physician immediately. SKIN: Flush affected area thoroughly with water. INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious person. Do not induce vomiting. Contact a physician immediately. INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.	
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: Yes, combustible if heated.	
FLASH POINT, °C: 56.7	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water ☒ Dry Chemical ☒ Carbon Dioxide ☒ Foam ☒ Other ☐	
SPECIAL FIRE FIGHTING PROCEDURES: not applicable	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, sulphur.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable ☒ Unstable ☐	
CONDITIONS TO AVOID: high temperature	
INCOMPATIBILITY (Material to Avoid) : Oxidizing materials	
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with oxidizing materials.	
REACTIVITY: Not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: RTECS, MSDS	PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200
PREPARATION DATE: January 6, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	