



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 95012

PRODUCT NAME: SUNLIGHT POT & PAN LIQUID**USE:** Manual Warewashing Detergent**SUPPLIER:**

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: B3 D2B**CHEMICAL FAMILY:** surfactant**TRADE NAME / SYNONYMS:** not applicable**CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Sodium dodecylbenzene sulphonate	10-30	025155-30-0	LD50 1260 mg/kg	oral/rat
Sodium lauryl ether sulphate	5-10	009004-82-4	LD50 1600 mg/kg	oral/rat
Ethanol	1-5	000064-17-5	LD50 7060 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:**Gloves:** not required**Eye:** not required**Footwear:** not required**Respiratory:** not required**Other:** not required**SPECIAL HANDLING PROCEDURES AND EQUIPMENT:** not applicable**VENTILATION REQUIREMENTS:** General ventilation**INCOMPATIBILITY (Material to Avoid):** Contact with cationic materials causes inactivation.**SPILL PROCEDURES:** Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.**WASTE DISPOSAL:** Dispose according to municipal, provincial, and federal regulations.**STORAGE / SHIPPING REQUIREMENT:** Store in a cool, dry area in a closed container. Avoid freezing.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear yellow liquid - lemon scent**S.G. / BULK DENSITY(g/cc):** 1.06**pH:** 7.0 ± 1.0**VAPOUR PRESSURE (mmHg):** not available**VAPOUR DENSITY (air=1):** not available**ODOUR THRESHOLD:** not available**BOILING POINT:** approx. 100°C**FREEZING POINT:** approx. 2°C**PERCENT VOLATILE:** approx. 66%**SOLUBILITY IN WATER:** soluble**EVAPORATION RATE (water=1):** not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**EYES:** May cause irritation.**SKIN:** Repeated or prolonged contact may result in irritation.**INGESTION:** May cause irritation of the digestive tract.**INHALATION:** No serious or irreversible effects expected.

LD50 (calculated): 5546 mg/kg		LC50 (calculated): not applicable	
OTHER TOXIC EFFECTS: TLV (Ethanol) TWA 1000 ppm, 1880 mg/m3			
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known			
VI - FIRST AID MEASURES			
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eye lids open while rinsing. Contact a physician immediately.			
SKIN: Flush affected area thoroughly with water.			
INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious person. Do not induce vomiting. Contact a physician immediately.			
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.			
VII - FIRE AND EXPLOSION DATA			
FLAMMABLE: Yes, combustible if heated.			
FLASH POINT, °C: 56.7		AUTO IGNITION TEMPERATURE, °C: N/Ap	
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []			
SPECIAL FIRE FIGHTING PROCEDURES: not applicable			
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, sulphur.			
EXPLOSIVE SENSITIVITY TO: not applicable			
VIII - REACTIVITY DATA			
STABILITY: Stable [X] Unstable []			
CONDITIONS TO AVOID: high temperature			
INCOMPATIBILITY (Material to Avoid) : Oxidizing materials			
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with oxidizing materials.			
REACTIVITY: Not dangerously reactive			
IX - MSDS PREPARATION			
SOURCES USED: RTECS, MSDS		PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200	
PREPARATION DATE: June 28, 2005			
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.			