



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 2980

PRODUCT NAME: LSP 570

USE: Automobile Polish Wax

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: D2B

CHEMICAL FAMILY: surfactant

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Sodium dodecylbenzene sulphonate	7-13	025155-30-0	LD50 1260 mg/kg	oral/rat
Sodium lauryl ether sulphate	7-13	068585-34-2	LD50 1700 mg/kg	oral/rat
Coconut diethanolamide	1-5	068603-42-9	LD50 2700 mg/kg	oral/rat
Ethanol	1-5	000064-17-5	LD50 7060 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: not required

Eye: safety glasses

Footwear: not required

Respiratory: not required

Other: not required

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye contact. Do not breathe mist or spray.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): oxidizing materials

SPILL PROCEDURES: Contain the spill. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Avoid freezing.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, pink liquid - cherry fragrance

S.G. / BULK DENSITY(g/cc): 1.034

pH: (concentrate): 8.0

VAPOUR PRESSURE (mmHg): not available

VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD: not available

BOILING POINT: approx. 100°C

FREEZING POINT: 0°C

PERCENT VOLATILE: 72%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): <1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause irritation. No serious or irreversible effects expected if treated promptly.

SKIN: Repeated or prolonged contact may result in irritation.

INGESTION: May cause irritation of the digestive tract.

INHALATION: No serious or irreversible effects expected.

LD50 (calculated): 4567 mg/kg		LC50 (calculated): not available	
OTHER TOXIC EFFECTS: TLV: Ethanol 100 ppm; Coconut Diethanolamide 9-3 ppm			
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known			
VI - FIRST AID MEASURES			
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician.		
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.		
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician.		
INHALATION:	Remove patient to fresh air.		
VII - FIRE AND EXPLOSION DATA			
FLAMMABLE: No.			
FLASH POINT, °C: not applicable		AUTO IGNITION TEMPERATURE, °C: N/Ap	
EXTINGUISHING MEDIA: Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other []			
SPECIAL FIRE FIGHTING PROCEDURES: not required			
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, sulphur, nitrogen.			
EXPLOSIVE SENSITIVITY TO: not applicable			
VIII - REACTIVITY DATA			
STABILITY: Stable [X] Unstable []			
CONDITIONS TO AVOID: keep from freezing			
INCOMPATIBILITY (Material to Avoid) : oxidizing materials			
HAZARDOUS DECOMPOSITION PRODUCTS: oxides of carbon			
REACTIVITY: not dangerously reactive			
IX - MSDS PREPARATION			
SOURCES USED: RTECS		PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200	
PREPARATION DATE: April 15, 2003			
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.			